



INVEST IN THE FUTURE



French manufacturer
since 1964

Celebrating

60

years of innovation
1964 - 2024

Chargers, Boosters & Starters

Charge & entretien des batteries

Batterieservicegeräte-Katalog

Caricabatterie, Booster & Avviatore

Catálogo de Cargadores

2024



CHARGERS - BSU - BOOSTERS - STARTERS - TESTERS - JUMPER CABLES - ACCESSORIES

A solid manufacturing group

900 people € 125 000 000

C1+
Credit Rating
Banque de France

55 000 m²
2 factories



INVEST IN THE FUTURE



French manufacturer since 1964

A family company




3 catalogues

3 500+ references



Welding, Plasma cutting & Induction heating



Car Body Welding Systems



Chargers, Boosters & Starters

A worldwide coverage

125 countries



 **GYS FRANCE**
Laval



 **GYS GERMANY**
Aachen



 **GYS U.K.**
Rugby



 **GYS CHINA**
Shanghai



 **GYS ITALIA**
Venezia



 **GYS IBERICA**
Madrid

CHARGERS

GYSFLASH Pb	6
GYSFLASH LITHIUM	9
GYSFLASH Pb / LITHIUM	10
GYSFLASH ON BOARD	16
ENERGYS	17
GYSFLASH PRO	18
ARTIC	32
ENERGY / TCB	33
CT / CA / WATTMATIC	34
BATIUM	36

BATTERY TESTERS, POWER INVERTER & PORTABLE ENERGY

TRADITIONAL TESTERS	64
DIGITAL TESTERS	64
TESTERS & PRINTER	66
POWER INVERTER	68
PORTABLE ENERGY	70

CHARGERS & STARTERS

START / NEOSTART	40
STARTIUM	42
DIAGSTARTIUM	43
STARTFLASH	44

JUMPER CABLES, EV CABLES & ACCESSORIES

JUMPER CABLES	74
EV CHARGING	75
ACCESSORIES	76

BOOSTERS

GYSPACK	48
STARTPACK	52
ENERGVSTATION	55
NOMAD POWER	58
STARTRONIC	60
GYSRAP	61

www.gys.fr



visit with





CHARGERS

6 - 12 - 16 - 24 - 36 - 48 V

GYSFLASH

GYSFLASH Pb	6
GYSFLASH LITHIUM	9
GYSFLASH Pb / LITHIUM	10
GYSFLASH ON BOARD	16

CONVERTER DC/DC

ENERGYS	17
---------	----

BATTERY SUPPORT UNIT

GYSFLASH PRO	18
GYSFLASH PRO CNT	20
CNT TECHNOLOGY & ACCESSORIES	26

MORE

ARTIC	32
ENERGY / TCB	33
CT / CA / WATTMATIC	34
BATIUM	36

GYSFLASH TECHNOLOGY



Save and load settings. Automatic restart in case of power cut.
Mémorisation des réglages. Redémarrage automatique en cas de coupure électrique.
Einstellungsspeicherung. Automatisches Starten nach einem Netzausfall.



Start/stop Engine :
Compatible with Start/Stop vehicles.
Compatible véhicules Start/Stop.
Geeignet für START-STOP- Fahrzeuge.



Can Bus ready: compatible with Can Bus Technology, the Gysflash can be connected to the motorcycle 12V socket (cable is optional).

Can bus ready : compatible avec la technologie Can Bus, le Gysflash se branche directement sur la prise 12 V de la moto (câble en option).

Can-Bus Ready: Mit der Can-Bus Technologie kompatibel. Das GYSFLASH wird direkt an den 12V-Anschluss des Motorrads angeschlossen (Kabel optional).



Auto Recovery : Recovers deeply discharged (min 2V) and/or sulfated batteries.

Auto Recovery : Récupération des éléments des batteries profondément déchargées (mini 2V) et/ou sulfatées.

Auto Recovery: Wiederherstellung der Zellen bei tiefentladenen bzw. sulfatierten Batterien (min. 2V).



“Cold charge” mode: performance-enhancing charging mode for cold or freezing weather conditions.

Mode “Cold charge”: optimisation des performances en cas de temps froid ou de gel.

-Cold Charge--Modus: Leistungsoptimierung bei kaltem Wetter oder bei Frost.



Fitted with a highly sensitive sensor, Gysflash automatically adjusts the charge based on ambient temperature.

Équipé d'un capteur haute sensibilité, le Gysflash ajuste automatiquement les paramètres de charge en fonction de la température ambiante.

Ausgestattet mit einem hochempfindlichen Sensor stellt das GYSFLASH automatisch die Ladeparameter der Umgebungstemperatur entsprechend ein.



Power supply mode: Optimum floating charge, ideal for use during battery change to protect vehicle memory.
Also for when the vehicle is not in use for extended periods or for demonstration use.

Source d'énergie : mode de maintien optimal de l'état de charge. Idéal pour les véhicules en hivernage, de démonstration, ou pour le remplacement de batterie.

Energiequelle: Aufrechterhaltung des Batteriezustands. Ideal für Saison-, Ausstellungsfahrzeuge oder bei Batteriewechsel.



GYSFLASH Pb

CHARGERS

SMART HF INVERTER Pb

BEST SELLER



12V

GYSFLASH 1.12

1 A



F FLASH Connector




029361
029514

GYSFLASH 4.12 & 4.12S

0.8/4 A



F FLASH Connector



4.12
029422
029521

4.12S (110 V)
069190
072701
072817

GYSFLASH 6.12

0.8/6 A



F FLASH Connector




029378
029613

GYSFLASH 8.12

8 A



S SAE Connector



029385
029545

GYSFLASH 12.12

12 A



S SAE Connector




029392
029552

SMART CHARGE

7 STEP / 8 STEP

1. Status analysis
2. Recovery
3. Test desulfation
4. Desulfation
5. Fast charge 80%
6. Absorption
7. Refresh (for "8 step" only)
8. Floating 100%



Rebalancing of the battery cells for greater longevity (not available on all models).
Rééquilibrage des cellules de la batterie pour plus de longévité (suivant modèle).
Regenerierung der Batteriezellen für eine längere Lebensdauer (je nach Modell).

110V



GYSFLASH 4.12 S
GYSFLASH 1.12 PL S



DISPLAY BOX
GYSFLASH 4.12 x 5
026001



DESIGN
GYS
FRANCE
MADE IN
GYS CHINA

PATENTS REGISTERED NUMBERS
002280008 & 002279927
EUROPEAN TRADEMAR & DESIGN

	 50 / 60 Hz		Power	 I _{charge}	 V	 Charge	 Maintenance		Ondulation/ Ripple	Charging curve		IP			 L × W × H cm / kg
GYSFLASH 1.12	220-240 V AC	1 m	18 W	1 A	12 V	2 > 32 Ah	2 > 100 Ah	<0.4 Ah/month	<150 mV Rms	IUoU	7 steps	IP 65	0.44 kg	13 × 8 × 3.8 cm	30 × 15.5 × 6 / 0.6
GYSFLASH 4.12	220-240 V AC	2 m	70 W	0,8/4 A	12 V	1.2 > 90 Ah	1.2 > 130 Ah	<0.4 Ah/month	<150 mV Rms	IUoU	7 steps	IP 65	0.69 kg	17 × 9 × 5.1 cm	34.5 × 17.9 × 36.2 / 0.89
GYSFLASH 4.12S	100-127 V AC														
GYSFLASH 6.12	220-240 V AC	2 m	90 W	0,8/6 A	12 V	1.2 > 125 Ah	1.2 > 170 Ah	<0.4 Ah/month	<150 mV Rms	IUoU	8 steps	IP 65	0.77 kg	19 × 10 × 5.2 cm	36 × 19.5 × 7 / 1
GYSFLASH 8.12	220-240 V AC	2 m	130 W	8 A	12 V	15 > 160 Ah	15 > 240 Ah	<0.4 Ah/month	<150 mV Rms	IUoU	8 steps	IP 65	0.85 kg	19 × 10 × 5.2 cm	36 × 19.5 × 7 / 1
GYSFLASH 12.12	220-240 V AC	2 m	195 W	12A	12 V	20 > 250 Ah	20 > 330 Ah	<0.4 Ah/month	<100 mV Rms	IUoU	8 steps	IP 65	1.1 kg	22.1 × 11.1 × 5.8 cm	36.4 × 20 × 6.8 / 1.3



GYSFLASH Pb

CHARGERS

SMART HF INVERTER Pb



YouTube



PLAYLIST
GYSFLASH



HERITAGE • 6/12V

GYSFLASH 6 HERITAGE

0.8/6A



F FLASH Connector



029538

6/12/24V

GYSFLASH 6.24

0.8/6A



F FLASH Connector



029460

029644

GYSFLASH 9.24

9A



S SAE Connector



029477

029651

GYSFLASH TECHNOLOGY



Save and load settings. Automatic restart in case of power cut.

Mémorisation des réglages. Redémarrage automatique en cas de coupure électrique.

Einstellungsspeicherung. Automatisches Starten nach einem Netzausfall.



Start/stop Engine :

Compatible with Start/Stop vehicles.

Compatible véhicules Start/Stop.

Geeignet für START-STOP- Fahrzeuge.



Can Bus ready: compatible with Can Bus Technology, the Gysflash can be connected to the motorcycle 12V socket (cable is optional).

Can bus ready : compatible avec la technologie Can Bus, le Gysflash se branche directement sur la prise 12 V de la moto (câble en option).

Can-Bus Ready: Mit der Can-Bus Technologie kompatibel. Das GYSFLASH wird direkt an den 12V-Anschluss des Motorrads angeschlossen (Kabel optional).



Auto Recovery : Recovers deeply discharged (min 2V) and/or sulfated batteries.

Auto Recovery : Récupération des éléments des batteries profondément déchargées (mini 2V) et/ou sulfatées.

Auto Recovery: Wiederherstellung der Zellen bei tiefentladenen bzw. sulfatierten Batterien (min. 2V).



Fitted with a highly sensitive sensor, Gysflash automatically adjusts the charge based on ambient temperature.

Équipé d'un capteur haute sensibilité, le Gysflash ajuste automatiquement les paramètres de charge en fonction de la température ambiante.


Ausgestattet mit einem hochempfindlichen Sensor stellt das GYSFLASH automatisch die Ladeparameter der Umgebungtemperatur entsprechend ein.

SMART CHARGE

7 STEP / 8 STEP / 8 STEP LiFePO4

Pb

1. Status analysis
2. Recovery
3. Test desulfation
4. Desulfation
5. Fast charge 80%
6. Absorption
7. Refresh (for "8 step" only)
8. Floating 100%




Rebalancing of the battery cells for greater longevity (not available on all models).

Rééquilibrage des cellules de la batterie pour plus de longévité (suivant modèle).

Regenerierung der Batteriezellen für eine längere Lebensdauer (je nach Modell).

LiFePO4 (LFP)

1. UVP Wake up - Status analysis
2. Recovery
3. Fast charge 90%
4. Absorption 95%
5. Test
6. Completion
7. Equalization
8. Floating 100%



UVP Wake up (Under Voltage Protection)

Battery reactivation when in UVP protection.

Réactivation de la batterie en protection UVP.

Reaktivierung der Batterie mit UVP-Schutz.



Equalizing Balancing System

Balancing of the battery cells.

Équilibrage des cellules.

Ausgleich der Batteriezellen.



GYSFLASH LITHIUM

LiFePO4



12V

GYSFLASH 1.12 Lithium

1A



F FLASH Connector




029675

GYSFLASH 6.12 Lithium

4/6A



F FLASH Connector



029729

 PATENTS REGISTERED NUMBERS 002280008 & 002279927 EUROPEAN TRADEMARK & DESIGN	 50 / 60 Hz	 Power	 I _{charge}	 V	 Charge	 Maintenance	 Z _z	Ondulation/Ripple	Charging curve	 IP	 IP	 ↕	 L × W × H cm / kg	
GYSFLASH 6 HERITAGE	220-240 V AC	2 m	90 W	0,8/6 A	6/12 V	1.2 › 125 Ah	1.2 › 170 Ah	<0.4 Ah /month	<150 mV Rms	IUoU	8 steps	IP 65	0.77 kg	19 × 10 × 5.2 cm 36.5 × 19.4 × 7 cm / 1
GYSFLASH 6.24	220-240 V AC	2 m	130 W	0,8/6 A	6/12 V	1.2 › 125 Ah	1.2 › 170 Ah	<0.4 Ah /month	<150 mV Rms	IUoU	7 step	IP 65	0.85 kg	19 × 10 × 5.2 cm 36.5 × 19.5 × 7 cm / 1
				0,8/4 A	24 V	1.2 › 100 Ah	1.2 › 140 Ah	<0.4 Ah /month	<150 mV Rms	IUoU	7 step	IP 65	0.85 kg	19 × 10 × 5.2 cm 36.5 × 19.5 × 7 cm / 1
GYSFLASH 9.24	220-240 V AC	2 m	190 W	9 A	6/12 V	18 › 220 Ah	18 › 300 Ah	<0.4 Ah /month	<100 mV Rms	IUoU	8 step	IP 65	1.1 kg	22.1 × 11.1 × 5.8 cm 36.5 × 19.5 × 7 cm / 1.3
				6 A	24 V	15 › 125 Ah	15 › 170 Ah	<0.4 Ah /month	<100 mV Rms	IUoU	8 step	IP 65	1.1 kg	22.1 × 11.1 × 5.8 cm 36.5 × 19.5 × 7 cm / 1.3

9

GYSFLASH LITHIUM

SMART HF INVERTER CHARGERS

DESIGN GYS FRANCE MADE IN GYS CHINA	 50 / 60 Hz	 Power	 I charge	 V	 Charge	 Maintenance	 Zz	Ondulatio / Ripple	Charging curve	 IP			L × W × H cm / kg		
GYSFLASH 1.12 Lithium	220-240 V AC	1 m	18 W	1 A	12 V	0.5 , 20 Ah	0.5 , 50 Ah	<0.4 Ah/ month	<150 mV Rms	IUoU	8 step	IP 65	0.44 kg	13 × 8 × 3.8 cm	29.7 × 15 × 5.7 / 0.6
GYSFLASH 6.12 Lithium	220-240 V AC	2 m	90 W	4/6 A	12 V	1.2 , 125 Ah	1.2 , 170 Ah	<0.4 Ah/ month	<150 mV Rms	IUoU	8 step	IP 65	0.77 kg	19 × 10 × 5.2 cm	36.5 × 19.5 × 7 / 1



GYSFLASH Pb / LITHIUM

CHARGERS


SMART HF
INVERTER

Pb/LiFePO₄

OPTION

Gysflash 18.12 PL,
30.12 PL, 20.12/24 PL,
10.36/48 PL

Magnetfix 20
026063



x4



INTENSIVE



SC SMART
COOLING
TECHNOLOGY

100% DUST PROOF



SILENT

IP 23

INDOOR /
OUTDOOR



INTENSIVE



SHOCK
RESISTANT


IP 65

INDOOR /
OUTDOOR

12V

GYSFLASH 1.12 PL & 1.12 PL S

1 A



1.12 PL
026902
027541

1.12 PL S (110 V)
070851
072794
072824

GYSFLASH 8.12 PL

1/4 / 8 A



069282

GYSFLASH 18.12 PL

7/12 / 18 A


GO > 2 V



026926

GYSFLASH 30.12 PL

7/15 / 30 A



029668
026070

GYSFLASH 32.12 PL

7/15 / 30 A



027381

GYSFLASH 20.12/24 PL

7/15 / 20 A



026049
027558

GYSFLASH 15.24 XTREM

15 A



025813

PATENTS REGISTERED NUMBERS 002280008 & 002279927 EUROPEAN TRADEMARK & DESIGN		 50 / 60 Hz		Power	I _{charge}	 V	 Charge	 Maintenance		Ondulation/ Ripple	Charg- ing curve		IP			 L × W × H cm / kg
DESIGN GYS FRANCE	GYSFLASH 1.12 PL	220-240 V AC	2 m	20 W	1 A	12 V	2 × 32 Ah (Pb) 0.5 × 20 Ah (LiFePO4)	2 × 100 Ah (Pb) 0.5 × 50 Ah (LiFePO4)	<0.4 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (LiFePo4)	IP 65	0,69 kg	17 × 9 × 5.1 cm	33 × 17.5 × 6 / 0.8
	GYSFLASH 1.12 PL S	100-127 V AC														
MADE IN GYS CHINA	GYSFLASH 8.12 PL	220-240 V AC	2 m	130 W	1/4/8 A	12 V	15 × 160Ah (Pb) 1.2 × 160 Ah (LiFePO4)	15 × 240Ah (Pb) 1.2 × 240 Ah (LiFePO4)	<0.4 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 65	0,85 kg	19 × 10 × 5.2 cm	—
MADE IN FRANCE	GYSFLASH 18.12 PL	220-240 V AC	2 m	300 W	7/12/18 A	12 V	15 × 270 Ah (Pb) 7 × 270 Ah (LiFePO4)		<0.5 Ah/month	<100 mV Rms	IUoU	7 step (Pb) 8 step (LiFePo4)	IP 33	1,55 kg	19 × 19 × 7.3 cm	30 × 22 × 9 / 1.9

 PATENTS REGISTERED NUMBERS 002280008 & 002279927 EUROPEAN TRADEMARK & DESIGN				Power						Ondulation/ Ripple	Charging curve		IP			
		50 / 60 Hz			I _{charge}	V	Charge	Maintenance								L × W × H cm / kg
MADE IN FRANCE	GYSFLASH 30.12 PL	220-240 V AC	2 m	500 W	7/15/30 A	12 V	15 > 375 Ah (Pb) 7 > 375 Ah (LiFePO4)		<0.5 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 33	1,85 kg	19 × 19 × 7.3 cm	30 × 22 × 9 / 2.2
	GYSFLASH 32.12 PL	230V	2.5 m	500W	7/15/30 A	12 V	10 > 400 Ah		<0.5 Ah/month	<150 mV Rms	IUoU	—	IP 23	4,7 kg	8 × 25 × 20 cm	36 × 27.5 × 20.5 / 4.6
	GYSFLASH 20.12/24 PL	220-240 V AC	2 m	500 W	7/15/20 A 7/15 A	12 V 24 V	15 > 300 Ah (Pb) 7 > 300 Ah (LiFePO4) 15 > 240 Ah (Pb) 7 > 240 Ah (LiFePO4)		<1 Ah/month	<150 mV Rms	IUoU	7 step (Pb) 8 step (LiFePO4)	IP 33	1,85 kg	19 × 19 × 7.3 cm	30 × 22 × 8.5 / 2.2
	GYSFLASH 15.24 XTREM	230V	2.5 m	500W	7/10/15 A	12/24 V	5 > 240 Ah		<1 Ah/month	<150 mV Rms	IUoU	—	IP 65	5.4 kg	7.5 × 25 × 21 cm	27 × 20 × 36 / 5.4

CONNECTORS

A complete solution • Une solution complète • Eine Komplettlösung



F Flash Connector GYSFLASH ≤ 6A : 1.12 / 4.12 / 6.12 / 6 Heritage / 6.24 / 1.12 Li / 6.12 Li / 1.12 PL

F1 / Clamps L 0.45 m (1.3 mm²) All 026889	F2 / Charge indicator L 0.56 m (1.3 mm²) All LEAD 029149	F3 / Eyelets ø M6 L 0.45 m (1.3 mm²) All 029194 ø M8 L 0.45 m (1.3 mm²) 027626	F4 / Charge indicator eyelets ø M6 L 0.56 m (1.3 mm²) All LEAD 029200	F5 / Cigarette lighter L 0.45 m (0.82 mm²) 029439	F6 / Cable L 2.50 m (1.3 mm²) All 029057	F7 / Connector MLX L 0.45 m (1.3 mm²) 027589	F8 Adapter S / F - F / S L 0.45 m (1.3 mm²) 027480	F9 Adapter F / A L 0.45 m (1.3 mm²) 025820

s SAE Connector GYSFLASH < 16A : 8.12 PL / 12.12 / 9.24 / 6.24 / 3.48 PL

S1 / Clamps L 1.50 m (1.3 mm²) All +Showroom Gysflash 1212 027688	S2 / Eyelets ø M6 L 0.45 m (1.3 mm²) 027466 ø M8 L 0.45 m (1.3 mm²) 027633 ø M10 L 0.45 m (1.3 mm²) 027640	S3 / XLR 3 pin L 0.45 m (1.3 mm²) 027428	S4 / T-Bar L 0.45 m (1.3 mm²) 027442	S5 Adapter S / A L 0.45 m (1.3 mm²) 027473	S6 KIT SAE / JACK (max 5 A) L 0.45 m (1.3 mm²) 025646	S7 / Cigarette lighter (max 10 A) Only for 8.12 PL L 0.45 m (1.3 mm²) 077331	S8 / Cable L 2.5 m (4 mm²) 077348

A ANDERSON Connector GYSFLASH < 40A : 18.12 PL / 30.12 PL / 20.12-24 PL / 10.36-48 PL

A1 / Clamps All L 1.90 m (4 mm²) 026094 L 6 m (4 mm²) 027435	A2 / Eyelets 4 mm² ø M6 L 0.40 m 027657 ø M8 L 0.40 m 027664 ø M8 L 1.90 m 027794 ø M10 L 0.40 m 027671	A3 / Anderson L 1.5 m (4 mm²) 027855

XTREM CABLES GYSFLASH 15.24 XTREM

2pts/NATO Spiral 5 m 028968	2pts/NATO 5 m - 4 mm² 025837	2pts/DIN14690 Emergency vehicle 5 m 028777

SELECT THE RIGHT GYSFLASH

CHOISISSEZ VOTRE GYSFLASH • WÄHLEN SIE IHR GYSFLASH AUS

SPECIAL PROJECT - CONTACT US

GYSFLASH						MEDICAL SERVICE - LEISURE				MOTORBIKE LIGHT MOBILITY				AUTO - CAMPER VAN - TRUCK								MARINE				INDUS TRY	URBAN
	6V	12V	24V	36V	48V																						

Pb																											
1.12																											
1.12 PL																											
4.12																											
6.12																											
8.12																											
8.12 PL																											
12.12																											
18.12 PL																											
30.12 PL																											
6 Heritage	6V	12V																									
6.24 PL			24V																								
20.12/24 PL			12V	24V																							
6.24																											
9.24																											
3/48 PL																											
10.36/48 PL																											

LiFePO4																											
1.12 Lithium																											
1.12 PL																											
6.12 Lithium																											
8.12 PL																											
18.12 PL																											
30.12 PL																											
6.24 PL																											
20.12/24 PL																											
3/48 PL																											
10.36/48 PL																											

Li-ion																											
6.24 PL																											
3/48 PL																											
10.36/48 PL																											

M = maintenance only

SPECIAL PROJECT - CONTACT US

Contact us for special projects. Quick customization :
CAN BUS / CAN Open / J1939 / NMEA 2000 / RS485 /
SM BVS / Automation / Relays...

SC

SMART COOLING TECHNOLOGY

100% DUST PROOF

SILENT

HIGH EFFICIENCY

Up to 15% Energy Saving

93%

EMC class B

ALU

RUST PROTECTION

ULTRA LIGHTWEIGHT

VIBRATION & SHOCK RESISTANT

-25 / +60°C

GYSFLASH PL-E TECHNOLOGIES

SSM

Save and load settings. Automatic restart in the event of a power cut.

Mémoire des réglages. Redémarrage automatique en cas de coupure électrique.

Einstellungsspeicherung. Automatisches Starten nach einem Netzausfall.

Auto Recovery

: Recovers deeply discharged (min 2V) and/or sulfated batteries.

Auto Recovery

: Récupération des éléments des batteries profondément déchargées (mini 2V) et/ou sulfatées.

Auto Recovery

: Wiederherstellung der Zellen bei tiefentladenen bzw. sulfatierten Batterien (min. 2V).

SMART CHARGE

Pb

1. Status analysis

2. Recovery

3. Test desulfation

4. Desulfation

5. Fast charge 80%

6. Absorption

7. Floating 100%

Pb TRACTION

1. Status analysis

2. Recovery

3. Sulphation test

4. Desulfation

5. Fast charge 80%

6. Absorption

7. Test Absorption

8. Refresh

9. Floating 100%

LiFePO4 (LFP) / Li-ion

1. Status analysis

2. Recovery

3. Fast charge 90%

4. Absorption 95%

5. Test

6. Completion

7. Equalization

8. Floating 100%

UVP Wake up (Under Voltage Protection)

Battery reactivation when in UVP protection.

Réactivation de la batterie en protection UVP.

Reaktivierung der Batterie mit UVP-Schutz.

Equalizing Balancing System

Balancing of the battery cells.

Équilibrage des cellules.

Ausgleich der Batteriezellen.

OUTDOOR - LEISURE

MOBILITY

MARINE

AGRI

MEDICAL

PROFESSIONAL

INDUSTRY

GYSFLASH ON BOARD

CHARGERS

ON BOARD

Pb

Lithium

NMC / LCO / MCO / NCA...

LiFePO4 / Li-ion / Li-Po

GYSFLASH 18.12 PL-E

21.5 cm

7 cm

17.5 cm

GYSFLASH 15.24 PL-E

21.5 cm

7 cm

17.5 cm

12V

GYSFLASH 18.12 PL-E

18 A

Pb / LFP

025806

12V

GYSFLASH 30.12 PL-E

30 A

Pb / LFP

COMING SOON

24V

GYSFLASH 15.24 PL-E

15 A

Pb / Traction / LFP / Li-ion

025943

36V

GYSFLASH 10.36 PL-E

10 A

Pb / Traction / LFP / Li-ion

025950

48V

GYSFLASH 8.48 PL-E

8 A

Pb / Traction / LFP / Li-ion

COMING SOON

OPEN & CONNECT

cables not included

4 pts connector included 3G 0.75 x 2.5 mm²

3 pts connector included max 2.5 mm² or AWG14

INCLUDED

Ø 5.5 mm

GYSFLASH 18.12 PL-E, 15.24 PL-E, 10.36 PL-E, 8.48 PL-E

Fixing Kit

INDUSTRIAL CHARGERS

COMING SOON

PB / Traction / LFP / Li-ion

CAN BUS / CAN OPEN / J1939 / NMEA 2000 / RS485 / SM BVS

GYSPOWER 24V : 15 A - 30 A - 50 A - 100 A

GYSPOWER 36V : 10 A - 20 A - 30 A

GYSPOWER 48V : 8 A - 25 A - 50 A

MADE IN FRANCE	50 / 60 Hz				START MINI	I max	25°C @ 100 %	40°C @ 100 %	50°C @ 100 %	60°C @ 100 %			Zz	Ondulation/ Ripple	IP			L x W x H cm / kg
GYSFLASH 18.12 PL-E	230V	12V	300W	2V	18 A	18 A	16 A	14 A	12.5 A		36 x 270 Ah	18 x 270 Ah	<0.4 Ah /month	<150 mV Rms	20	1.3 kg	21.5 x 17.5 x 7 cm	30 x 27 x 13 / 1.7
GYSFLASH 30.12 PL-E	230V	12V	500W	2V	30 A	30 A	27 A	23 A	18 A		60 x 400 Ah	30 x 400 Ah	<0.4 Ah /month	<150 mV Rms	20	1.6 kg	21.5 x 8 x 17.5 cm	—
GYSFLASH 15.24 PL-E	230V	24V	500W	2V	15 A	15 A	13.5 A	11.5 A	9 A		30 x 240 Ah	15 x 240 Ah	<0.4 Ah /month	<150 mV Rms	20	1.6 kg	21.5 x 8 x 17.5 cm	29 x 13 x 27 / 2
GYSFLASH 10.36 PL-E	230V	36V	500W	2V	10 A	10 A	9 A	7.5 A	6 A		20 x 230 Ah	10 x 230 Ah	<0.4 Ah /month	<150 mV Rms	20	1.6 kg	21.5 x 8 x 17.5 cm	—
GYSFLASH 8.48 PL-E	230V	48V	500W	2V	8 A	8 A	7 A	6 A	5 A		15 x 160 Ah	8 x 160 Ah	<0.4 Ah /month	<150 mV Rms	20	1.6 kg	21.5 x 8 x 17.5 cm	—

ENERGY

ON BOARD POWER INVERTER

DC > DC REVERSIBLE

Pb

Lithium

Liquid / Gel, AGM

LiFePO4

NEW

09 / 2023

ENERGY DC/DC 50.12 / 24

50 A

072534

Bat. input	Bat. output	Solar input	EFFICIENCY	Zz		
U	I max	U	I max	U _{MPPT}	I max	
12/24V	50A	12/24V	50A	9-30V	20A	98%

ENERGY DC/DC 50.12/24

OPEN & CONNECT

Terminals included

Auxiliary connector included

cables not included

EURO 6 STANDARD

when starting the vehicle

ALTERNATOR

IN

OUT

MORE OUTPUT POWER

PARALLEL CHARGING

50 A + 50 A + 50 A

150 A

DOUBLE CHARGING

WITH GYSFLASH

vehicle stopped

max 5 A

IN

OUT

WITH SOLAR PANEL

MPPT integrated (Max Power Point Tracker)

max 5 A

IN

OUT

SOLAR PANEL

NEW

08 / 2023

foldable

0.5 m

1.2 m

SOLAR PANEL

monocrystalline - ETFE quality

18V - 100 W max

OUTPUT

USB 1 : 5V/3A

USB 2 : 5V/3A ; 9V/2A ; 12V/1.5A

Type C : 5V/3A ; 9V/2A ; 12V/1.5A

Jack : 18V/5.6A max

compatible with Energys DC/DC 50.12/24

079410

17

ENERGY

ON BOARD CHARGERS

SC

SMART COOLING
TECHNOLOGY

100%
DUST
PROOF

SILENT

SMART 9 STEP

Pb

1. Status analysis

2. Recovery

3. Sulphation test

4. Desulfation

5. Fast charge 80%

6. Absorption

7. Refresh

8. Floating 100%

LiFePO₄

7 steps

1. Status analysis

2. Recovery

3. Fast charge 90%

4. Absorption 95%

5. Completion

6. Equalization

7. Floating 100%

CHARGE

Pb AUTOMOTIVE

✓ GEL

✓ AGM

✓ LIQUID

✓ EASY

✓ EXPERT

Pb TRACTION

✓ GEL

✓ LIQUID

LITHIUM READY

✓ LFP/LiFePO₄

BSU

DIAG +

U2
ADJUSTABLE

SHOWROOM

CHANGE BATTERY

POWER SUPPLY

U2 & I2 max
ADJUSTABLE

GYSFLASH PRO

CHARGERS

BSU

& CHARGERS

BATTERY SUPPORT UNIT

YouTube

PLAYLIST
GYSFLASH
PRO

10.5 cm

PFC

POWER FACTOR
CORRECTION

FV

FLEXIBLE
VOLTAGE

85 V — 265 V

Select mode

Select parameters

Adjust values

22
languages

GB DK CZ

FR FI PL

DE TR SK

NL HR UA

ES GR

PT HU

IT CN simplified

RU CN traditional

SE JP

12 V

GYSFLASH 30.12

30 A

PFC SC

2,5 m - 6 mm²

029224

GYSFLASH 50.12 FV

50 A

PFC FV SC

2,5 m - 10 mm²

026056

GYSFLASH 100.12

100 A

PFC SC

2,5 m - 16 mm²

029071

029453

5 m - 16 mm²

029415

029002

6 / 12 / 24 V

GYSFLASH 30.24

30 A

PFC SC

2,5 m - 6 mm²

029231

GYSFLASH 50.24

50 A

PFC SC

2,5 m - 10 mm²

029095

5 m - 16 mm²

029620

12 V

GYSFLASH 102.12

100 A

PFC SC

5 m - 16 mm²

029606

ACCESSORIES p.30

MADE IN FRANCE	50 / 60 Hz	L	mm ²			START MINI	I _{max}	25°C @ 100 %	40°C @ 100 %		TRACTION BATTERIES		SHOWROOM CONNECT	IP				L × W × H cm / kg
GYSFLASH 30.12	185 > 265 V	2,5 m	6	12V	540 W	2 V	30 A	30 A	30 A	10 > 400 Ah	—	Ø M6	21	4.9 kg	25.5 × 10.5 × 23 cm	41.4 × 25 × 31.1 / 4.9		
GYSFLASH 50.12 FV	85 > 265 V	2,5 m	10	12V	850 W	2 V	50 A	50 A	40 A	10 > 600 Ah	—	Ø M6	21	6.6 kg	30 × 10.5 × 29 cm	40 × 24 × 30 / 6.6		
GYSFLASH 100.12	185 > 265 V	2,5 m 5 m	16	12V	1600 W	2 V	100 A	75 A	66 A	20 > 1200 Ah	—	Ø M6	21	7.4 kg 8.3 kg	32 × 10.5 × 29.2 cm	31 × 25 × 41 / 7.4		
GYSFLASH 30.24	185 > 265 V	2,5 m	6	6 V 12 V 24 V	540 W	2 V	30 A 30 A 15 A	30 A 30 A 15 A	30 A 30 A 15 A	10 > 400 Ah 10 > 200 Ah	•	Ø M6	21	4.9 kg	25.5 × 10.5 × 23 cm	41.5 × 24.3 × 31 / 4.9		
GYSFLASH 50.24	185 > 265 V	2,5 m 5 m	10 16	6 V 12 V 24 V	1600 W	2 V	50 A	50 A 45 A	45 A 40 A 35 A	10 > 600 Ah	•	Ø M6	21	6.6 kg 7.9 kg	30 × 10.5 × 29.2 cm	41 × 24.5 × 31 / 6.6		
GYSFLASH 102.12	185 > 265 V	5 m	16	12V	1600 W	2V	100 A	75 A	66 A	20 > 1200 Ah	—	Ø M6	21	9.1 kg	12 × 34.5 × 29.5 cm	24 × 40 × 30 / 9.1		

19

GYSFLASH PRO

BSU & CHARGERS

18



GYSFLASH PRO CNT

CHARGERS

BSU & CHARGERS

BATTERY SUPPORT UNIT

CNT
Connected
Technology

FULL
CUSTOMIZABLE
p.26


PFC POWER FACTOR
CORRECTION

16 V COMPATIBLE WITH
16V BATTERIES

FV FLEXIBLE
VOLTAGE
85 V 10 V 265 V

22 languages

GB RU GR CN simplified
FR SE CZ CN traditional
DE DK PL JP
NL FI SK UA
ES TR HR
PT HU



10.5 cm
51.12 CNT
101.12 CNT

13 cm
121.12 CNT FV
125.12CNT FV
101.24 CNT FV
51.48 CNT FV

12 V (factory preset)
16/24 V READY

Use custom configuration tool
(detail p.26)

IP 41
1mm

IP 40
1mm

12 V

GYSFLASH 51.12 CNT FV

50 A

PFC FV SC CNT

2,5 m - 10 mm²
068179



GYSFLASH 101.12 CNT

100 A

PFC SC CNT

2,5 m - 16 mm²
025790
5 m - 16 mm²
026988



GYSFLASH 121.12 CNT FV

120 A

PFC FV CNT

5 m - 25 mm²
026971
027756
071605



GYSFLASH 125.12 CNT FV

120 A

120 A @ 100%

PFC FV CNT

5 m - 25 mm²
028883



6 / 12 / 16 / 24 V

GYSFLASH 101.24 CNT FV

100 A

PFC FV CNT

16 V
5 m - 25 mm²
025967



6 / 12 / 16 / 24 / 36 / 48 V

GYSFLASH 51.48 CNT FV

50 A

PFC FV CNT

16 V
2,5 m - 16 mm²
072015



SC

SMART
COOLING
TECHNOLOGY


100%
DUST
PROOF



SILENT



SMART 9 STEP



CHARGE (150 CURVES CAPACITY)

Pb AUTOMOTIVE

- ✓ GEL
- ✓ AGM
- ✓ LIQUID
- ✓ EASY
- ✓ NORMAL
- ✓ BOOST
- ✓ RECOVERY+
- ✓ and more

Pb TRACTION

- ✓ GEL
- ✓ LIQUID
- ✓ and more

LITHIUM

- ✓ LFP/LiFePO₄
- ✓ LI-ION STD
- ✓ LFP CELL+
- ✓ LI-ION CELL+
- ✓ and more

BSU (10 CURVES CAPACITY)

DIAG +

SHOWROOM

CHANGE BATTERY

POWER SUPPLY

AND MORE

✓ TEST

- ✓ VOLTAGE
- ✓ START UP
- ✓ ALTERNATOR

✓ STARTER

- ✓ START

CNT

Connected
Modules
& Technology
p.26



MADE IN FRANCE	 50 / 60 Hz		 mm ²			 START MINI	 I max	 25°C @100 %	 40°C @ 100 %		 TRACTION BATTERIES	 SHOWROOM CONNECT	IP			 L x W x H cm / kg
GYSFLASH 51.12 CNT FV	85 > 265 V	2,5 m	10	12V 24V	850 W	1 V	50 A 25 A	50 A 25 A	40 A 20 A	10 > 600 Ah 10 > 300 Ah	●	Ø M6	41	6.8 kg	30 x 10.5 x 29 cm	38.5 x 22 x 40.5 / 6.8
GYSFLASH 101.12 CNT	185 > 265 V	2,5 m 5 m	16	12V	1600 W	1 V	100 A	75 A	66 A	20 > 1200Ah	●	Ø M6	21	7.5 kg 8.3 kg	32 x 10.5 x 29.2 cm	38.5 x 20 x 40.5 / 7.5 35.5 x 23 x 35 / 8.6
GYSFLASH 121.12 CNT FV	85 > 265 V	5 m	25	12V	2000 W	1 V	110 V : 100 A 230 V : 120 A	75 A 110 A	55 A 90 A	20 > 1200Ah	●	Ø M6	20	10.4 kg	31 x 13 x 26 cm	35.5 x 23 x 35 / 10.4
GYSFLASH 125.12 CNT FV	85 > 265 V	5 m	25	12V	2000 W	1 V	110 V : 100 A 230 V : 120 A	100 A 120 A	77 A 116 A	20 > 1200Ah	●	Ø M6	40	10.9 kg	31 x 13 x 26 cm	38.5 x 22 x 40.5 / 10.9
GYSFLASH 101.24 CNT FV	85 > 265 V	5 m	25	6/12V 24V	3200 W	1 V	110 V : 100 A 230 V : 100 A 110 V : 50 A 230 V : 100 A	72 A 89 A 50 A 76 A	47 A 68 A 35 A 59 A	20 > 1200Ah	●	Ø M6	20	10.6 kg	31 x 13 x 26 cm	38.5 x 22 x 40.5 / 10.6
GYSFLASH 51.48 CNT FV	85 > 265 V	2,5 m	16	6/12/24V 36/48V	3200 W	1 V	110 V : 50 A 230 V : 50 A 110 V : 25 A 230 V : 50 A	44 A 49 A 26 A 45 A	21 A 39 A 19 A 35 A	10 > 600 Ah	●	Ø M6	20	9 kg	31 x 13 x 26 cm	41 x 22 x 38.5 / 9



GYSFLASH PRO CNT

CHARGERS

BSU & CHARGERS

BATTERY SUPPORT UNIT

CNT
Connected
Technology

FULL
CUSTOMIZABLE
p.26



22 languages

GB NL IT DK HR PL UA CN simplified
FR ES RU FI GR SK CN traditional
DE PT SE TR CZ HU JP

PFC POWER FACTOR
CORRECTION

16 V COMPATIBLE WITH
16V BATTERIES

FV FLEXIBLE
VOLTAGE

85 V 265 V
110 V 230 V

TRACTION



NEW



12 V

6 / 12 / 16 / 24 V

6 / 12 / 16 / 24 / 36 / 48 V

GYSFLASH 103.12 CNT

100 A

PFC SC CNT

5 m - 16 mm²
072008



GYSFLASH 123.12 CNT FV

120 A

PFC FV CNT

5 m - 25 mm²
025677



GYSFLASH 103.24 CNT FV

100 A

PFC FV CNT 16 V

5 m - 25 mm²
025684



GYSFLASH 25.48 CNT FV

25 A

PFC SC FV CNT 16 V

2,5 m - 10 mm²
075962



GYSFLASH 53.48 CNT FV

50 A

PFC FV CNT 16 V

2,5 m - 16 mm²
025998



SC

SMART
COOLING
TECHNOLOGY


100%
DUST
PROOF



SILENT



SMART 9 STEP




CHARGE (150 CURVES
CAPACITY)

Pb AUTOMOTIVE
✓ GEL
✓ AGM
✓ LIQUID
✓ EASY
✓ NORMAL
✓ BOOST
✓ RECOVERY+
✓ and more

Pb TRACTION
✓ GEL
✓ LIQUID
✓ and more

LITHIUM
✓ LFP/LiFePO₄
✓ LI-ION STD
✓ LFP CELL+
✓ LI-ION CELL+
✓ and more

BSU (10 CURVES CAPACITY)



✓ TEST
✓ VOLTAGE
✓ START UP
✓ ALTERNATOR

✓ STARTER
✓ START

CNT

Connected
Modules
& Technology
p.26



MADE IN FRANCE	 50 / 60 Hz	 L ↕	 mm²			START MINI	I max	25°C @ 100 %	40°C @ 100 %		 TRACTION BATTERIES	 SHOWROOM CONNECT	IP			 L × W × H cm / kg
GYSFLASH 103.12 CNT	185 › 265 V	5 m	16	12 V	1600 W	1 V	100 A	75 A	66 A	20 › 1200 Ah	—	Ø M6	21	8.2 kg	34.5 × 29.5 × 12 cm	41 × 38.5 × 22 / 9.2
GYSFLASH 123.12 CNT FV	85 › 265 V	5 m	25	12 V	2000 W	1 V	110 V : 100 A 230 V : 120 A	100 A 120 A	85 A 120 A	20 › 1200 Ah	●	Ø M6	30	11 kg	34 × 25 × 15 cm	35.5 × 23.5 × 35 / 11
GYSFLASH 103.24 CNT FV	85 › 265 V	5 m	25	6/12 V	3200 W	1 V	110 V : 100 A 230 V : 100 A	100 A 100 A	68 A 79 A	20 › 1200 Ah	●	Ø M6	30	11 kg	34 × 25 × 15 cm	35 × 23 × 37 / 11
			24 V	110 V : 50 A 230 V : 100 A			50 A 95 A	47 A 72 A								
GYSFLASH 25.48 CNT FV	100 › 127 V	2,5 m	10	6/12/24 V	800 W 800 W	1 V	110 V : 12 A 230 V : 25 A	19 A 23,5 A	12 A 22 A	10 › 300 Ah	●	Ø M6	21	7,8 kg	12 × 34.5 × 29.5 cm	40.5 × 38 × 22.5 / 8.8
	220 › 240 V			36/48 V	800 W 1600 W		3A 24 A	10 A 20 A								
GYSFLASH 53.48 CNT FV	85 › 265 V	2,5 m	16	6/12/24 V	3200 W	1 V	110 V : 50 A 230 V : 50 A	50 A 50 A	28 A 41 A	10 › 600 Ah	●	Ø M6	30	9,5 kg	34 × 25 × 15 cm	40 × 39 × 23 / 9.5
				36/48 V			110 V : 25 A 230 V : 50 A	26 A 48 A	20 A 37 A							



GYSFLASH PRO CNT

CHARGERS

BSU & CHARGERS
BATTERY SUPPORT UNIT

CNT
Connected
Technology

**FULL
CUSTOMIZABLE**
p.26

PFC POWER FACTOR
CORRECTION

FV FLEXIBLE
VOLTAGE
85 V $\longleftrightarrow$ 265 V
110 V 230 V
GYSFLASH 148.12 CNT FV

FV FLEXIBLE
VOLTAGE
320V $\longleftrightarrow$ 520V
400 V 480 V
GYSFLASH 158.12 CNT FV

19 languages

GB IT HR
FR RU GR
DE SE CZ
NL DK PL
ES FI SK
PT TR UA

**INDUSTRY /
PRODUCTION**

25

GYSFLASH PRO CNT

BSU & CHARGERS

NEW



IP 54

**DUST
&
SPLASH
PROTECTION**



**NATURAL
CONVECTION**



NEW



12 V



YouTube

**PLAYLIST
CNT TECHNOLOGY**

GYSFLASH 148.12 CNT FV

145 A

1 ~

PFC SC FV CNT

069916

GYSFLASH 158.12 CNT FV

150 A

3 ~

SC FV CNT

069909

SC

**SMART
COOLING
TECHNOLOGY**


**100%
DUST
PROOF**



SILENT



SMART 9 STEP



CHARGE (150 CURVES
CAPACITY)

Pb AUTOMOTIVE
✓ GEL
✓ AGM
✓ LIQUID
✓ EASY
✓ NORMAL
✓ BOOST
✓ RECOVERY+
✓ and more

Pb TRACTION
✓ GEL
✓ LIQUID
✓ and more

LITHIUM
✓ LFP/LiFePO₄
✓ LI-ION STD
✓ LFP CELL+
✓ LI-ION CELL+
✓ and more

BSU (10 CURVES CAPACITY)

DIAG +
U2 ADJUSTABLE

POWER SUPPLY
U2 & I2 max
ADJUSTABLE


AND MORE

✓ TEST
✓ VOLTAGE
✓ START UP
✓ ALTERNATOR

✓ STARTER
✓ START


CNT

Connected Modules & Technology
p.26



I/O

PLC connection



Contact us for use

MADE IN FRANCE

	50 / 60 Hz	L mm	mm ²			START MINI	I max	25°C @ 100 %	40°C @ 100 %	60°C @ 100 %		TRACTION BATTERIES	SHOWROOM CONNECT	IP		
GYSFLASH 148.12 CNT FV	85 > 265V	5 m	25	12V	2500W	1V	110V : 100 A 230V : 145 A	100 A 134 A	90 A 116 A	62 A 88 A	20 > 1200 Ah 20 > 1800 Ah	•	Ø M6	54	9.4 kg	37.6 × 14.5 × 29.6 cm
GYSFLASH 158.12 CNT FV	320 > 520V	5 m	25	12V	2500W	1V	150 A	140 A	120 A	100 A	20 > 1800Ah	•	Ø M6	54	10.3 kg	37.6 × 14.5 × 38 cm




CHARGERS

BSU & CHARGERS

BATTERY SUPPORT UNIT

CNT
Connected
Technology



SOFTWARE UPDATE

LIFETIME EVOLUTION



TRACEABILITY

CHARGING DATA



DESIGN YOUR CHARGING CURVE

PRODUCT CONFIGURATION (CONFIG CURVE / LOGISTIC / CHARGING CURVE)


CNT MANAGER (gys.fr)

- GYSFLASH parameters
- Custom curves
- Multi products management
- Import/export configurations
- ...



Full customisation

Create your online specific configuration



Adjust your product to your charging needs

	LEAD-ACID - PB	Lithium - LFP	Lithium - Li-ion std
VOLTAGE CELL (20% - 100%)	2.0 V/cell – 2.15 V/cell	3.2 V/cell – 3.6 V/cell	3.5 V/cell – 4.2 V/cell
CHARGING VOLTAGE	2.33 V/cell – 2.47 V/cell	3.6 V/cell	4.2 V/cell
Gysflash xx.12 CNT	1 S* – 6 S	1 S – 4 S	1 S – 3 S
Gysflash xx.24 CNT	1 S – 12 S	1 S – 8 S	1 S – 7 S
Gysflash xx.48 CNT	1 S – 24 S	1 S – 16 S	1 S – 14 S

*S = Battery serial cells

Download a GYS specific configuration

Configuration file (gys.fr)	Applications	CHARGE MODE												POWER MODE						MISCELLANEOUS		
		Pb-CHARGE						Li-CHARGE				TRACTION		SHOWROOM	DIAG+	CHANGE BAT.	STARTER MODE	POWER SUPPLY	LI-SUPPLY/LFP	LI-SUPPLY/LI-Ion	TESTER MODE	
		normal	AGM	liquid	Easy	Boost	Recovery + Ca / a recov	LFP / LifePO4	Li-Ion std	LFP cell+	Li-Ion cell+	liquid	gel									
1_gys_original.gfc	Initial configuration of the charger	✓	✓	✓	✓			✓						✓	✓							✓
2_car_extended.gfc	Extensive features for garages	✓	✓	✓	✓	✓		✓						✓	✓	✓	✓	✓				✓
3_showroom_only.gfc	Simplified version for dealerships and demonstration vehicles													✓								
4_pro_lithium.gfc	Professional of lithium battery							✓	✓	✓	✓							✓	✓	✓		
5_traction.gfc	Forklift truck, electric pallet truck, stacker...											✓	✓									
6_full_version.gfc	Full version	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓



YouTube
PLAYLIST
CNT TECHNOLOGY



Contact us for special projects.

Quick Customization:
Modes, Curves, parameters...

MODULES

EXTREME MODULARITY

SINGLE MODULE




MULTI MODULES



ADVANCED




MULTI MODULES GROUPS



PARALLEL CHARGING

EXAMPLE : GYSFLASH 101.12 CNT (X4)





CHARGERS

BSU & CHARGERS

BATTERY SUPPORT UNIT

CNT
Connected
Technology

COMING SOON



and More...



NEW

NEW CNT-SCM
Smart Can Module



Scratch
fixation



Magnetic
fixation


SMART COMMUNICATION

INCLUDED

CNT-SUM
Smart USB Module
025974

USB micro A
↳ 6.9 × 6.8 × 2.9 cm / ▲ 85g
☞ 28.5 × 11 × 11.5 cm / ▲ 380g

Computer /
Diag System




SMC Cable
1 m
056596



CNT-SWM
Smart Wireless Module
070837

Bluetooth Wifi
COMING
SOON
↳ 6.9 × 6.8 × 2.9 cm / ▲ 85g
☞ 27.6 × 9.6 × 9.6 cm / ▲ 440g

Computer /
Diag System



SMC Cable
1 m
056596



LIGHT & SOUND

INCLUDED

CNT-SLM
Smart Light Module
027978



65dB



Pb charge



Lithium charge



OK



Error

↳ 12.6 × 14.6 × 9.3 cm / ▲ 560g
☞ 23 × 17 × 13 cm / ▲ 840g

SMC Cable
1 m
056596



PRINT & SCAN

INCLUDED

CNT-SPM
Smart Printer Module
026919

↳ 14 × 10.5 × 13.3 cm / ▲ 1.4 kg
☞ 23 × 17 × 13 cm / ▲ 1.9 kg




OPTIONS

Support
Barcode scanner
025745



USB Barcode scanner
1D/2D
027718



SMC Cable
1 m
056596



Standard roller x2
57mm x 7.5 m, Ø 25 mm
056633



USB Keyboard

AZERTY 027725
QWERTY 027770

QWERTZ compatibility



SMC CABLE

1 m
056596

3 m
025691



YouTube

PLAYLIST
CNT TECHNOLOGY

SMART HUB MODULE

INCLUDED

CNT-SHM
Smart Hub Module
025981

↳ 22 × 18 × 4.5 cm / ▲ 1 kg
☞ 16.4 × 13.4 × 24 cm / ▲ 1.7 kg

SMC Cable
1 m
056596



UP TO 4 MODULES + 4 GYSFLASH



POWER HUB MODULE

CNT-PHM
Power Hub Module
056589

↳ 31.7 × 24.5 × 9 cm / ▲ 2.7 kg
☞ 32 × 29 × 13.5 cm / ▲ 3.2 kg

4 GYSFLASH IN
Ø Cables: 10 → 25 mm²

GYSFLASH CNT Connected GYSFLASH CNT Connected GYSFLASH CNT Connected GYSFLASH CNT Connected

INCLUDED
M6 KIT



OUT Ø Cables: 25 → 70 mm²



CHARGERS

STANDARD ACCESSORIES



Anderson Cables		Anderson/NATO		Anderson↔Rema 160 A		Anderson↔Anderson 175 A		Anderson↔Texas	
for GYSFLASH	Anderson/Clamps	Anderson/NATO		Anderson↔Rema 160 A		Anderson↔Anderson 175 A		Anderson↔Texas	
	2.5 m - 16 mm ² 056503	2.5 m - 16 mm ² 026810		5 m - 16 mm ² 069091		5 m - 16 mm ² 069107		0.2 m - 16 mm ² 055902	
	5 m - 16 mm ² 054615							1 m - 16 mm ² 028791	
	8 m - 16 mm ² 056572								
30.12 / 50.12 100.12 / 101.12 102.12 / 32-12 PL	✓	✓		—		—		✓	
30.24 / 50.24	✓	✓		✓		✓		✓	
53.48	✓	✓		✓		✓		—	



Texas Cables		Texas/Rema 160 A		Texas/Anderson 175 A		Texas/NATO	
for GYSFLASH	Texas/Clamps	Texas/Rema 160 A		Texas/Anderson 175 A		Texas/NATO	
	2.5 m - 25 mm ² 028876	5 m - 16 mm ² 025714		5 m - 25 mm ² 025721		5 m - 25 mm ² 025707	
	5 m - 25 mm ² 027886					10 m - 25 mm ² 056626	
101.24 / 121.12 123.12 / 103.24 125.12	✓	✓		✓		✓	

PARALLEL CABLES KIT

072954

Anderson/Cable lugs M6
x2
16 mm²
1 m

+

Cable lugs/Cable lugs M6
x2 (1 red + 1 black)
35 mm²
5 m

+

Texas/Cable lugs M6
x2
25 mm²
1 m


+

M6 KIT
Ø16 (x4)
Ø25 (x4)
Ø35 (x4)

+

SMC Cable - 1 m


CONNECTORS



NATO
026780

DIN14690
028784

INTERNAL FUSES



40 A
for GYSFLASH 30
054546

80 A
for GYSFLASH 40, 50
054653

125 A
for GYSFLASH 100, 101, 102
054585

150 A
for GYSFLASH 121, 123, 103
027930

EXTERNAL FUSES



6.3 A
GYSFLASH 30
054578

10 A
GYSFLASH 40, 50, 100, 101, 102
056527

SUPPORTS



Wall support
- Tablette
Wandhalterung
055513

Heavy-duty case
Valise de chantier
Hartschalenkoffer
060432


21 × 43 × 57 cm / 3.9 kg
36 × 43 × 20 cm / 3.3 kg



Battery charger
Support chargeur
Ladeständer
079595

NEW

Wall support for GYSFLASH
32.12 PL, 102.12, 123.12, 103.12, 103.24, 15.24 XTREM, 25.48, 53.48



INCLUDED
Fixation

OPTION
Magnetfix 50
029637

CONFIGURATION (Trolley - Chariot - Fahrwagen)



ALL GYSFLASH
- COMPATIBILITY -

VERTICAL

HORIZONTAL

Trolley - Chariot
Fahrwagen
028890

SLM/SPM support
028906

Cable support
052284

GYSFLASH CNT PACKS

	101.12 CNT	121.12 CNT	CNT-SPM + roller + support	Barcode Scanner + support		Trolley	CNT SLM	CNT SHM	CNT PHM	Parallel cables kit
pack GYSFLASH CNT 1 068117	✓	—	✓	✓	✓ QWERTY	✓	—	—	—	—
pack GYSFLASH CNT 2 068124	✓	—	✓	✓	✓ AZERTY	✓	—	—	—	—
pack GYSFLASH CNT 3 068131	—	✓	✓	✓	✓ QWERTY	✓	—	—	—	—
pack GYSFLASH CNT 4 068148	—	✓	✓	✓	✓ AZERTY	✓	—	—	—	—
NEW pack GYSFLASH CNT 5 072978	✓ x2	—	✓	✓	✓ AZERTY	✓	✓	✓	✓	✓
NEW pack GYSFLASH CNT 6 074972	✓ x2	—	✓	✓	✓ QWERTY	✓	✓	✓	✓	✓
NEW pack Parallel Charging 072961	—	—	—	—	—	—	—	✓	✓	✓
NEW pack GYSFLASH PRO 1 079908	—	—	✓	✓	✓ AZERTY	✓	✓	✓	—	—
NEW pack GYSFLASH PRO 2 079915	—	—	✓	✓	✓ QWERTY	✓	✓	✓	—	—



ARTIC

ENERGY

TCB



IP 65

WATER
PROTECTION
ARTIC 1500, 4000 & 8000

CHARGERS ONLY



SSM

Save and load settings.
Automatic restart in case of
power cut.

Mémorisation des réglages.
Redémarrage automatique en
cas de coupure électrique.

Einstellungsspeicherung.
Automatisches Starten nach
einem Netzausfall.

START
STOP

Start/stop Engine :
Compatible with Start/Stop
vehicles.
Compatible véhicules Start/Stop.
Geeignet für START-STOP-
Fahrzeuge.



"Cold charge" mode:
performance-enhancing
charging mode for cold or
freezing weather conditions.

Mode "Cold charge":
optimisation des performances
en cas de temps froid ou de gel.

-Cold Charge--Modus:
Leistungsoptimierung
bei kaltem Wetter oder bei Frost.



AUTOMATIC SMART HF INVERTER

REGULATED
IUoU
FAST CHARGE

ARTIC 800

12V 0.8A GO > 7V

SSM

029569

029682



ARTIC 1500

12V 1.5A GO > 7V

SSM

029576

029699



ARTIC 4000

6/12V 4/1-4A GO > 2V (6V)
GO > 7V (12V)

SSM

029583

029705



ARTIC 8000

2/8A 12V GO > 7V

SSM

029590

029712



12V • TRADITIONAL

W

ENERGY 124

3A

SSM

023215



ENERGY 126

4A

SSM

023222

025165



12V • AUTOMATIC

WU

TCB 60

2/4A GO > 3.5V

SSM

023253

025189



TCB 90

2/5.5A GO > 3.5V

SSM

023260

025202



TCB 120

3.5/7A GO > 3.5V

SSM

023284

025240



Fuse X10
10A
054530

15A
054493

RECOMMENDATION	5 Ah			10 Ah			15 Ah			20 Ah			6V			40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ Ah
	6V	12V	24V																					
Maintenance																								
ARTIC 800																								
ARTIC 1500																								
ARTIC 4000																								
ARTIC 8000																								
ENERGY 124																								
ENERGY 126																								
TCB 60																								
TCB 90																								
TCB 120																								

INCLUDED

all ARTIC

Eyelets /
Céillets /
Ösen
30 cm
026872


Clamps /
Pincés /
Klemmen
35 cm
026865



CA




9 A



12A



10 A



25 A

12/24 V • MANUAL **W**

12/24 V • AUTOMATIC W2

MULTICHARGE



32 A



026087

12/24/36/48 V • MANUAL **W**

WATTMATIC



5 A



024823

: 025417

$G0 > 3.5 \text{ V}$

1.5 m - 1.5 mm²  40 A

9 A



025608

: 025622

$G0 > 3.5 \text{ V}$

1.5 m - 2.5 mm²  40 A

10 A



025615

: 025639

$G0 > 3.5 \text{ V}$

1.8 m - 2.5 mm²  40 A

6/12V • AUTOMATIC **WUoU**

	5 Ah			10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ A
RECOMMENDATION	6V	12V	24V												
CT 160		•	•					12 V : 25 > 160 Ah - 24 V : 15 > 90 Ah							
CT 210		•	•					12 V : 35 > 210 Ah - 24 V : 20 > 100 Ah							
MULTICHARGE CT 48		•	•	+48 V							12, 24, 36 V : 90 > 450 Ah - 48 V : 70 > 360 Ah				
CA 150		•	•					35 > 150 Ah							
CA 360		•	•					40 > 350 Ah							
WATTMATIC 100	•	•						15 > 100 Ah							
WATTMATIC 140	•	•						20 > 150 Ah							
WATTMATIC 170	•	•						25 > 180 Ah							



CHARGERS & STARTERS

12 - 24 V

TRADITIONAL

START	40
NEOSTART	41

AUTOMATIC

STARTIUM	42
----------	----

BATTERY SUPPORT UNIT

DIAGSTARTIUM	43
STARTFLASH	44



STARTUP

CHARGERS & STARTERS

AUTOMATIC **W2**



SELF START
MEMORY



12 V

STARTUP 80

17 A



024922
025127



START / NEOSTART

CHARGERS & STARTERS

TRADITIONAL **W**



SELF START
MEMORY



12V

12/24V

START 200

18 A



1.5 m - 6 mm² → 60 A
025530



START 300

23 A



2 m - 10 mm² → 220 A
025547



NEOSTART 320

9 / 40 A



2 m - 10 mm² → 220 A
025301



12/24V

NEOSTART 420

40 A



1.8 m - 10 mm² → 500 A
025295
025479



NEOSTART 620

60 A



1.8 m - 16 mm² → 500 A
025288
025486



Fuse
x2



50 A
Start 200
054622
80 A
Start 300
054653



150 A
Neostart 320
054639
200 A
Neostart 420, 620
054547

RECOMMENDATION

	6V	12V	24V	5 Ah	10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ Ah
START UP 80		•						35 > 50 Ah								
START 200		•						35 > 40 Ah	40 > 80 Ah							
START 300		•	•					35 > 50 Ah	50 > 100 Ah							
NEOSTART 320		•	•						35 > 60 Ah	60 > 120 Ah						
NEOSTART 420		•	•				Precharge (± 10 min)			35 > 80 Ah	80 > 160 Ah					
NEOSTART 620		•	•							45 > 100 Ah	100 > 200 Ah					

CHARGERS & STARTERS

AUTOMATIC

IWUoU



YouTube
PLAYLIST
STARTIUM

3 in 1

AUTOMATIC CHARGE
= BATTUM

AUTOMATIC START

TEST ALTERNATOR

TIMER

UNIVERSAL MODE

AUTO SELECTION

SULFATED BATTERIES

ALL BATTERIES

>1V

FULL PROTECTION

On-board electronics

Over voltage

No sparks



CHARGERS & STARTERS

AUTOMATIC
& BSU

IWUoU

BATTERY SUPPORT UNIT

BSU Battery Support Unit

POWER SUPPLY
DIAG+ 60A

Voltage adjustable 12 V · 15 V



12/24 V

STARTIUM 330E

25 A

1,9 m - 10 mm² ➤ 500 A

026469

STARTIUM 480E

40 A

1,9 m - 16 mm² ➤ 600 A

026483
☎ : 025578

STARTIUM 680E

45 A

2,2 m - 25 mm² ➤ 600 A

026490
☎ : 025585

STARTIUM 980E

50 A

2,5 m - 35 mm² ➤ 600 A

026506

Disconnectable

12V

12/24 V

DIAG STARTIUM 60-12

60 A

2,2 m - 25 mm² ➤ 600 A

026513

DIAG STARTIUM 60-24

60 A

2,2 m - 25 mm² ➤ 600 A

026520
☎ : 025592

MADE IN FRANCE		I ₁			CHARGE 							START 			BSU				CCA I (EN) START	
	50/60 Hz		CHARGE kW	START kW		min › max	RMS / Efficace	Average / Moyen (EN 60335)		Boost	Automatic		1V/C	0V/C		AUTO START				
STARTIUM 330E	230V	16 A	0,8	6,5	12V 24V	20 › 370 Ah 20 › 300 Ah	40 A	25 A	4	—	●	12 V : 24 V :	165 A 130 A	270 A 210 A	●	—	100 A	26 x 26 x 47 / 15.5	28 x 28 x 47 / 16	500 A
STARTIUM 480E	230V	16 A	1,7	9	12V 24V	20 › 600 Ah 20 › 450 Ah	65 A	30 A	4	40 A	●	12 V : 24 V :	280 A 210 A	390 A 290 A	●	—	200 A	34 x 30 x 64 / 20.5	64 x 37 x 31 / 29	750 A
STARTIUM 680E	230V	16 A	2	10	12V 24V	20 › 675 Ah 20 › 525 Ah	75 A	30 A	4	45 A	●	12 V : 24 V :	380 A 270 A	550 A 380 A	●	—	200 A	34 x 30 x 64 / 25.5	65 x 37 x 31 / 31	900 A
STARTIUM 980E	230V	16 A	2	12	12V 24V	20 › 750 Ah 20 › 525 Ah	80 A	40 A	4	50 A	●	12 V : 24 V :	500 A 400 A	720 A 560 A	●	—	250 A	34 x 30 x 80 / 30	65 x 37 x 32 / 36	1400 A
DIAG STARTIUM 60-12	230V	16 A	2	10	12V	20 › 900 Ah	95 A	60 A	4	—	●	12 V : 6 V :	310 A —	440 A —	●	●	200 A	35 x 35 x 72 / 30.5	80 x 37 x 35 / 36	900 A
DIAG STARTIUM 60-24	230V	16 A	2	10	6V	20 › 900 Ah	65 A	40 A	4	—	—	—	—	—	●	●	200 A	35 x 35 x 72 / 30.5	80 x 37 x 35 / 36	900 A
					12V	20 › 900 Ah	95 A	60 A			●	12 V : 24 V :	300 A 280 A	430 A 410 A						
					24V	20 › 525 Ah	65 A	40 A			●									

Fuse x2

100 A
Startium 330E
054394

200 A
Startium 480E, 680E,
Diag. 60-12, 60-24
054547

250 A
Startium 980E
055568

RECOMMENDATION

6V

12V

24V

5 Ah

10 Ah

15 Ah

20 Ah

40 Ah

80 Ah

90 Ah

110 Ah

120 Ah

180 Ah

240 Ah

300 Ah

+ Ah

STARTIUM 330E

STARTIUM 480E

STARTIUM 680E

STARTIUM 980E

DIAG STARTIUM 60-12

DIAG STARTIUM 60-24

40 · 80 Ah

80 · 120 Ah

40 · 120 Ah

120 · 160 Ah

50 · 180 Ah

180 · 200 Ah

50 · 240 Ah

50 · 180 Ah

180 · 200 Ah

Precharge (± 10 min)



STARTFLASH

CHARGERS & STARTERS

AUTOMATIC & BSU

CNT Connected Technology


BATTERY SUPPORT UNIT

SPECIAL PROJECTS

Contact us for special projects.
Quick Customization:
Modes, Curves, parameters...

22 languages

GB RU GR CN simplified
FR SE CZ CN traditional
DE DK PL JP
NL FI SK
ES TR UA
PT HR
IT HU



4 in 1

AUTOMATIC CHARGE

Pb AUTOMOTIVE

- ✓ GEL
- ✓ AGM
- ✓ LIQUID
- ✓ EASY
- ✓ EXPERT
- ✓ NORMAL
- ✓ BOOST
- ✓ RECOVERY+

Pb TRACTION

- ✓ GEL
- ✓ LIQUID

LITHIUM READY

- ✓ LFP/LiFePO₄
- ✓ LI-ION STD
- ✓ LFP CELL+
- ✓ LI-ION CELL+

BSU

DIAG +




SHOWROOM



CHANGE BATTERY



POWER SUPPLY




AUTOMATIC STARTER

✓ START

TEST

- ✓ VOLTAGE
- ✓ START UP
- ✓ ALTERNATOR



UNIVERSAL MODE AUTO SELECTION

SULFATED BATTERIES

ALL BATTERIES

GO >1V

PFC POWER FACTOR CORRECTION
185 V ← 265 V
110 V 230 V

1 WORLD PREMIERE

NEW



6/12/24 V

STARTFLASH 120.24 CNT

2 • 300 A

5 m - 35 mm² 700 A
073616

OPTION



Trolley
074965



Texas/Clamps
2.5 m - 25 mm² 028876
5 m - 25 mm² 027886



Texas/Rema 160 A
5 m - 16 mm² 025714



Texas/Anderson 175 A
5 m - 25 mm² 025721




Texas/NATO
5 m - 25 mm² 025707
10 m - 25 mm² 056626

CNT

Connected Technology


SOFTWARE UPDATE



CUSTOMIZATION




TRACEABILITY




Connected Modules & Technology p.26



SMART 9 STEP



1. Status analysis
2. Recovery
3. Sulphation test
4. Desulfation
5. Fast charge 80%
6. Absorption
7. Test Absorption
8. Refresh
9. Floating 100%



1. Status analysis
2. UVP Wake Up
3. Recovery
4. Fast charge 90%
5. Absorption 95%
6. Test
7. Completion
8. Equalization
9. Floating 100%

UVP Wake up (Under Voltage Protection), Battery reactivation when in UVP protection
EBS Equalizing Balancing System 100%Perfect charge

STARTER RECOMMENDATION



STARTFLASH 120

• • •

10 • 180 Ah

Précharge

180 • 250 Ah

MADE IN FRANCE



START MINI

I max

25°C @100 %

40°C @100 %



TRACTION BATTERIES

6/12/24 V

150 A

0V/C

AUTO START

IP

LxWxH cm / kg

LxWxH cm / kg

STARTFLASH 120.24 CNT

85 > 265 V

6/12/24 V

3500 W

2 V

110 V : 100 A

75 A

55 A

230 V : 120 A

110 A

90 A

20 • 1200 Ah

•

6 V :

300 A

12 V :

300 A

24 V :

200 A

300 A

•

20

49 x 37.5 x 30.5 / 14

41.5 x 32.5 x 25.5 / 18.5

STARTFLASH

CHARGERS & STARTERS

45

GYS



BOOSTERS

6 - 12 - 24 V

Pb inside

GYSPACK	48
STARTPACK	52
ENERGYSTATION	55

LITHIUM inside

NOMAD POWER	58
-------------	----

SUPER CAPACITOR inside

STARTRONIC	60
GYSCAP	61

BOOSTERS

Pb / LEAD

POWER SUPPLY
12V DC



12 V

18 Ah

INSIDE

HOBBIES
OCCASIONAL

PRO
INTENSIVE

GYSPACK 400

1 250 A

480 A
1V/C

0.6 m - 16 mm²

300 A

025455

025516

GYSPACK AIR

1 250 A

480 A
1V/C

1.1 m - 25 mm²

500 A

026322

OPTION

MEMORY AUTO SAVE
CABLE OBD 1,5 m
054202

Fuse 7,5 A

 Après chaque utilisation After each use Nach jeder Anwendung DESIGN BY FRANCE MADE IN FRANCE	 OFF	Après chaque utilisation After each use Nach jeder Anwendung	 Inside	 START	 1V/C	 Cranking CC	 Peak Battery	 ON OFF	 CC	 Fuse	 AIR	 Power Supply	 EXTERNAL Charge 230 V	 TEST OK	 LxWxH cm / kg	 LxWxH cm / kg
	GYSPACK 400	12V-18 Ah	12V	480 A	900 A	1250 A	—	—	—	—	⌚ 12 V DC/0,5A	12 V DC/1,2A	●	26 x 13. x 29.5 / 6.4	28.5 x 16 x 34 / 7.2	
	GYSPACK AIR	12V-18 Ah	12V	480 A	900 A	1250 A	●	●	—	4 bars	⌚ 12 V DC/0,5A	12 V DC/1,2A	●	33 x 17 x 37 / 8.5	38.5 x 22 x 44 / 9.4	
	GYSPACK 600	12V-22 Ah	12V	550 A	1050 A	1750 A	—	—	—	—	⌚ 12 V DC	12 V DC/1,2A	●	25.5 x 14 x 29.5 / 7.5	29.5 x 16. x 35.5 / 8.2	
	GYSPACK PRO	12V-22 Ah	12V	600 A	1100 A	1750 A	●	●	—	—	⌚ 12 V DC	12 V DC/1,2A	●	35 x 14 x 37 / 9	39 x 17 x 45 / 9.5	
	GYSPACK HERITAGE 6/12	6V- 2 x 20 Ah	6V 12V	400 A 450 A	800 A 850 A	3200 A 1600 A	●	●	1 x 300 A	—	⌚ 12 V DC	12 V DC/2A	●	36 x 11 x 45 / 13	39 x 22 x 51 / 14	

COMPRESSOR

Air Kit
included
4 bars

12 V

= 6 C*

24 V

= 12 C*

6 C* + 6 C*

*C = cells, cellules



12 V

22 Ah

INSIDE

HOBBIES
OCCASIONAL

PRO
INTENSIVE

GYSPACK 600

1 750 A

550 A
1V/C

0.6 m - 16 mm²

300 A

027336

027497

GYSPACK PRO

1 750 A

600 A
1V/C

1.1 m - 25 mm²

500 A

026155

025523

INCLUDED GYSPACK 400 / AIR / 600 / PRO

CHARGER

⊕ Power in 110-240 V / out 12 V
50/60 Hz
054677
054660

FLEXIBLE
VOLTAGE

85 V — 265 V

HERITAGE

6 / 12 V



6 / 12 V

20 Ah

20 Ah

INSIDE

HOBBIES
OCCASIONAL

PRO
INTENSIVE

GYSPACK HERITAGE 6/12

6 V

3 200 A

400 A
1V/C

12V

1 600 A

450 A
1V/C

1.8 m - 25 mm²

600 A

025844

INCLUDED GYSPACK Heritage

CHARGER

⊕ Power in 110-240 V / out 12 V
50/60 Hz
054684
054691

FLEXIBLE
VOLTAGE

85 V — 265 V

RECOMMENDATION	6V			12V			24V			5 Ah	10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ Ah
	6V	12V	24V	6V	12V	24V	6V	12V	24V	6V	12V	15V	20V	40V	80V	90V	110V	120V	180V	240V	300V	+ Ah
GYSPACK AUTO / 400		•																				
GYSPACK AIR		•																				
GYSPACK 600		•																				
GYSPACK PRO		•																				
GYSPACK HERITAGE	•	•																				

BOOSTERS

Pb/LEAD

INSIDE

POWER SUPPLY
12V DC



12 V

28 Ah

INSIDE

HOBBIES

OCCASIONAL

PRO

INTENSIVE

GYSPACK 660

1 900 A

640 A

1V/C

1.3 m - 25 mm²

➤

600 A

027862

🇬🇧: 027879

INCLUDED GYSPACK 660



CHARGER

⚡ Power in 100-240 V / out 12 V

50/60 Hz

027992

🇬🇧: 025929



REGULATED

I_{VoU}

FAST CHARGE

FV

FLEXIBLE VOLTAGE

85 V

265 V

FOR GYSPACK 660/750/800/700/900

Fuse

x2

200 A

054547

300 A

054561



OPTION

MEMORY AUTO SAVE

CABLE OBD 1,5 m

054202



Fuse 7,5A



12 V

28 Ah

INSIDE

HOBBIES

OCCASIONAL

PRO

INTENSIVE

GYSPACK 750

2 500 A

750 A

1V/C

1.3 m - 25 mm²

➤

600 A

026179

🇬🇧: 026353

INCLUDED GYSPACK 750



CHARGER

⚡ Power in 110-240 V / out 12 V

50/60 Hz

054684

🇬🇧: 054691



REGULATED

I_{VoU}

FAST CHARGE

FV

FLEXIBLE VOLTAGE

85 V

265 V



12 V

28 Ah

INSIDE

HOBBIES

OCCASIONAL

PRO

INTENSIVE

GYSPACK PRO 800

2 500 A

700 A

1V/C

1.8 m - 25 mm²

➤

600 A

068759

🇬🇧: 072107

INCLUDED GYSPACK PRO 800



CHARGER

⚡ Power in 110-240 V / out 12 V

50/60 Hz

054684

🇬🇧: 054691



REGULATED

I_{VoU}

FAST CHARGE

FV

FLEXIBLE VOLTAGE

85 V

265 V

12 V

16 Ah

INSIDE

HOBBIES

OCCASIONAL

PRO

INTENSIVE

GYSPACK PRO 700

1 800 A

640 A

1V/C

1.4 m - 25 mm²

➤

600 A

027077

🇬🇧: 027947

INCLUDED GYSPACK PRO 700



CHARGER

⚡ Power in 110-240 V / out 12 V

50/60 Hz

054684

🇬🇧: 027947



REGULATED

I_{VoU}

FAST CHARGE

FV

FLEXIBLE VOLTAGE

85 V

265 V

12 V

30 Ah

INSIDE

HOBBIES

OCCASIONAL

PRO

INTENSIVE

GYSPACK PRO 900

3 100 A

830 A

1V/C

1.8 m - 35 mm²

➤

600 A

027084

🇬🇧: 027954

INCLUDED GYSPACK PRO 900



CHARGER

⚡ Power in 110-240 V / out 12 V

50/60 Hz

054684

🇬🇧: 027954



REGULATED

I_{VoU}

FAST CHARGE

FV

FLEXIBLE VOLTAGE

85 V

265 V



DESIGN GYS FRANCE

MADE IN GYS CHINA

MADE IN FRANCE

 Inside	 START				 TEST / OK	 CHARGER INSIDE	 50 / 60 Hz	 EXTERNAL Charge 230V	 Protection		 Power out		 Fuse	 Fuse	 LxWxH cm	 LxWxH cm / kg
		1V/C	Cranking CC	Peak Battery								Memory				
28 Ah	12V	640 A	1200 A	1900 A	●	—	110-240 V	12V/2 A DC	●	●	 12V DC	—	1 × 200 A	35 x 19 x 40	39 x 23 x 45 / 13.5	
28 Ah	12V	750 A	1450 A	2500 A	●	—	110-240 V	12V/2 A DC	●	●	 12V DC	—	2 × 200 A	35 x 19 x 40	39 x 23 x 45 / 13.5	
28 Ah	12V	700 A	1320 A	2500 A	●	—	110-240 V	12V/2 A DC	●	●	 12V DC	10 A	2 × 200 A	31 x 19 x 35	32 x 23 x 37 / 18.4	
16 Ah	12V	640 A	1200 A	1800 A	●	●	220-240 V	—	●	●	 12V DC	10 A	1 × 200 A	33 x 15 x 32	35 x 24 x 36 / 12	
30 Ah	12V	830 A	1700 A	3100 A	●	●	220-240 V	—	●	●	 12V DC	10 A	1 × 300 A	33 x 15 x 32	35 x 24 x 36 / 16	

	5 Ah	10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ Ah
RECOMMENDATION	6V	12V	24V										
GYSPACK 660	•												
GYSPACK 750	•												
GYSPACK PRO 800	•												
GYSPACK PRO 700	•												
GYSPACK PRO 900	•												

BOOSTERS

Pb / LEAD



POWER SUPPLY
12V DC



12/24 V  INSIDE  HOBBIES PRO
OCCASIONAL INTENSIVE

STARTPACK TRUCK			STARTPACK TRUCK MOBILE		
12V	3 200 A	750 A 1V/C	12V	3 200 A	750 A 1V/C
24V	1 600 A	650 A 1V/C	24V	1 600 A	650 A 1V/C
1.8 m - 25 mm ²  600 A 025448  : 026339			1.8 m - 25 mm ²  600 A 026025  : 028807		

INCLUDED **STARTPACK TRUCK & TRUCK MOBILE**

DESIGN GYS FRANCE			START 						CHARGER INSIDE 	EXTERNAL Charge 230V 	Protection		Power out					
				1 V/C	Cranking CC	Peak Battery												
MADE IN GYS CHINA	STARTPACK TRUCK	2 × 22 Ah	12V	750 A	1450 A	3200 A	●	110 - 240 V	—	12 V/2 A DC	●	●	 12 V DC	—	1 × 300 A	37 x 20 x 46	39 x 22 x 50 / 18	
	/ TRUCK MOBILE		24V	650 A	1300 A	1600 A							 12 V DC	—		37 x 20 x 57	39 x 24 x 60 / 21	
MADE IN FRANCE	STARTPACK 12.24 CI	2x 16 Ah	12V	900 A	1700 A	3600 A	—	220 - 240 V	4 A	—	●	●	—	—	1 × 300 A	26 x 20 x 48	34 x 20 x 51 / 19	
	24V		700 A	1350 A	1800 A													
	STARTPACK PRO 12.24 CI	2x 30 Ah	12V	1300 A	2400 A	6200 A	—	220 - 240 V	4 A	—	●	●	—	—	1 × 300 A	14 x 35 x 56	63 x 39 x 30 / 34	
	24V		1200 A	2250 A	3100 A													

 YouTube



PLAYLIST
STARTPACK

GYS STARTPACK START BOOSTER 12/24 V

HIGH TECHNOLOGY INTERNAL BATTERY

RECHARGE 1

7 STEPS INTEGRATED SMART CHARGER

CHARGE 4 A

New handle design

EnerSys

TPPL TECHNOLOGY
Thin Plate
Pure Lead

PREMIUM QUALITY BATTERIES

GYS STARTPACK PRO CI 12.24

31x93x55 cm

BOOSTERS • Pb/LEAD INSIDE

Diagram illustrating the connection of two 16Ah batteries in parallel to a 12/24V system. The resulting capacity is 32Ah.

12/24 V 16Ah + 16Ah INSIDE HOBBIES OCCASIONAL PRO INTENSIVE

STARTPACK 12.24 CI

12V

3600 A

900 A
1V/C

24 V

★

1 800 A

700 A
1V/C

1.8 m - 35 mm²

➤ 600 A

024991

 : 068155

STARTPACK PRO 12.24 CI

12V

6200 A

1300 A
1V/C

24V

★★★

3100 A

1200 A
1V/C

2 m - 50 mm²

➤ 600 A

028920

 : 068162

INCLUDED **STARTPACK 12.24 & PRO 12.24**

This section contains three items:

- Fuse x2**: A yellow fuse box with two fuses. The first fuse is labeled **200 A 054547** and the second is labeled **300 A 054561**.
- INTEGRATED CHARGER**: A black plug icon next to the text **INTEGRATED CHARGER** and **7 STEP** inside a grey box.
- OFF**: A warning symbol (a triangle with a plug inside) and the text **OFF** below it. To the right of the symbol, it says: **Après chaque utilisation**, **After each use**, **Nach jeder Anwendung**.

				5 Ah		10 Ah		15 Ah		20 Ah		6V		40 Ah		80 Ah		90 Ah		110 Ah		120 Ah		180 Ah		240 Ah		300 Ah		+ Ah	
 RECOMMENDATION		6V	12V	24V																											
STARTPACK TRUCK			•	•										› 150 Ah																	
STARTPACK TRUCK MOBILE			•	•										› 150 Ah																	
STARTPACK 12.24 CI			•	•										› 160 Ah																	
STARTPACK PRO 12.24 CI			•	•										› 220 Ah																	

STARTPACK

BOOSTERS

Pb/LEAD

INSIDE

PRO

★★★

YouTube

PLAYLIST

STARTPACK

SMART STARTER MANAGEMENT SYSTEM

FULL PROTECTION

On-board electronics

Reverse polarity

Over voltage

No sparks

AUTO DETECT

Microprocessor Control

TIMER Adjustable

Battery voltage detection

Microprocessor Control

TIMER Adjustable

HIGH QUALITY BATTERIES

INCLUDED

GYSFLASH XL 6.12

1.9 m

1.9 m

6 A - Advanced technology 8 step smart charge

7 STEP

12/24 V

50Ah SPIRAL

+

50Ah SPIRAL

INSIDE

HOBBIES

OCCASIONAL

PRO +++ INTENSIVE

STARTPACK PRO 12.24 XL

12V

8 500 A

1600 A 1V/C

24 V

1 400 A

2 600 A

4 250 A

1400 A 1V/C

2 m - 70 mm² 1000 A 026711

OFF	After each use Après chaque utilisation Nach jeder Anwendung				START		CHARGE		CHARGER	Protection			LxWxH cm	LxWxH cm / kg
	Inside	12 V	1 V/C	Cranking CC	Peak Battery	min	max	min	max	ON	OFF	Fuse		
STARTPACK PRO 12.24 XL	2x 50 Ah	12 V	1 600 A	3 000 A	8 500 A	—	—	•	6 A outside	• automatic	•	300 A	2 m ø 70 mm ²	106 x 32 x 35
ENERGY STATION FP		12 V	1 400 A	2 600 A	4 250 A	12/24 V	100 > 375 Ah (x2)	•	30 A inside	• manual	•	300 A	2,5 m ø 50 mm ²	70 x 65 x 91



ENERGY STATION


Charger integrated

Autonomous booster

Charge external batteries 12V only

Recommended ENERGY STATION FP : 2 x 120 x 170 Ah

Batteries not provided
- Batteries non fournies
- Ohne Batterie geliefert



FULL PROTECTION

On-board electronics

Over voltage

No sparks

Reverse polarity



12/24 V

HOBBIES

OCCASIONAL

PRO INTENSIVE +++

ENERGY STATION FP 069589

INTEGRATED CHARGER

6 STEP

RECOMMENDATION	12V	24V	5 Ah	10 Ah	15 Ah	20 Ah	40 Ah	80 Ah	90 Ah	110 Ah	120 Ah	180 Ah	240 Ah	300 Ah	+ Ah
	•	•													
STARTPACK PRO 12.24 XL															
ENERGY STATION FP	-	-													

SELECT THE RIGHT BOOSTER
CHOISISSEZ VOTRE BOOSTER • WÄHLEN SIE IHREN BOOSTER AUS

6/12V		12 V									12-24 V				
GYSPACK HERITAGE		GYSPACK 400	GYSPACK AIR	GYSPACK 600	GYSPACK PRO	GYSPACK 660	GYSPACK PRO 700	GYSPACK 750	GYSPACK PRO 800	GYSPACK PRO 900	STARTPACK TRUCK/ TRUCK MOBILE	STARTPACK 12.24 CI	STARTPACK PRO 12.24 CI	STARTPACK PRO 12.24 XL	ENERGY STATION FP
025844		025455	026322	027336	026155	027862	027077	026179	068759	027084	025448 / 026025	024991	028920	026711	069589
	6 V	12 V									12 V	12 V	12 V	12 V	12 V
	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	12 V	24V	24V	24V	24V	24V
	1V/C	400 (6 V)	480 A									750 (12 V)	900 A (12 V)	1300 A (12 V)	1600 A (12 V)
	CC	450 (12 V)	480 A	480 A	550 A	600 A	640 A	640 A	750 A	700 A	830 A	650 (24 V)	700 A (24 V)	1200 A (24 V)	1400 A (24 V)
	PEAK	800 (6 V)	900 A	900 A	1050 A	1100 A	1200 A	1200 A	1450A	1320 A	1700 A	1450 A (12 V)	1700 A (12 V)	2400 A (12 V)	3000 A (12 V)
		850 (12 V)	900 A	900 A	1050 A	1100 A	1200 A	1200 A	1450A	1320 A	1700 A	1300 A (24 V)	1350 A (24 V)	2250 A (24 V)	2600 A (24 V)
	3200 (6 V)	1250 A									3200 A (12 V)	3600 A (12 V)	6200 A (12 V)	8500 A (12 V)	
	1600 (12 V)	1250 A	1250 A	1750 A	1750 A	1900 A	1800 A	2500 A	2500 A	3100 A	1600 A (24 V)	1800 A (24 V)	3100 A (24 V)	4250 A (24 V)	
2 x 20 Ah		18 Ah	18 Ah	22 Ah	22 Ah	28 Ah	16 Ah EnerSys	28 Ah	28 Ah	30 Ah EnerSys	2 x 22 Ah	2 x 16 Ah EnerSys	2 x 30 Ah EnerSys	2 x 50 Ah EXIDE TECHNOLOGIES	
		outside 2 A	outside 0,5 A	outside 0,5 A	outside 0,5 A	outside 0,5 A	inside 2 A	outside 2 A	outside 2 A	inside 2,5 A	outside 2 A	inside 4 A	inside 4 A	outside 6 A	inside 30A
		IUoU	WU	WU	WU	WU	IUoU	7 step	IUoU	IUoU	7 step	7 step	7 step	7 step	6 step
		12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC	12 V DC				
		1,8 m ø25 mm²	0,6 m ø16 mm²	1,1 m ø25 mm²	0,6 m ø16 mm²	1,1 m ø25 mm²	1,3 m ø25 mm²	1,4 m ø25 mm²	1,3 m ø25 mm²	1,8 m ø25 mm²	1,8 m ø25 mm²	1,8 m ø35 mm²	2 m ø50 mm²	2 m ø70 mm²	2,5 m ø50 mm²
		37×20×46	26×10×29	33×17×37	26×10×29	35×14×37	35×19×40	33×15×32	35×19×40	31×19×35	33×15×32	37×20×46/ 37×20×57	34×18×46	63×39×30	112×35×43
		18 kg	6,5 kg	8,5 kg	6,5 kg	9 kg	13,5 kg	12 kg	13,5 kg	18,4 kg	16 kg	18/21 kg	22 kg	34 kg	68 kg



OFF
After each use
Après chaque utilisation
Nach jeder Anwendung
CAUTION ON STAND BY
Keep your GYSPACK connected to the mains supply.

ATTENTION HORS UTILISATION
Laisser le chargeur branché en permanence.
ACHTUNG WENN NICHT IN GEBRAUCH
Ladegerät dauernd angeschlossen lassen.
ATTENTION CUANDO ESTA APAGADO
Dejar el cargador conectado permanentemente.
OPGELET BUITEN GEBRUIK
Laat de lader onafgebroken aangesloten.



NATO / OTAN : PRODUITS COMPATIBLES
Compatible Products - Kompatible Produkte



NATO ID / NCAGE : F8154 CG730



	GYSLASH 30.12, 50.12 FV 100.12, 101.12 CNT 30.24, 50.24 102.12, 32-12PL	GYSLASH 101.24 CNT FV 121.12 CNT FV	GYSLASH 123.12 CNT FV 103.24 CNT FV	GYSLASH 53.48 CNT FV	GYSLASH 15.24 XTREM	STARTIUM 980E	STARTPACK PRO 12.24 XL
NATO CONNECTOR 026780	✓	—	—	✓	—	—	—
Anderson/NATO 5 m - 16 mm² 026810	✓	—	—	✓	—	—	—
Texas/NATO 5 m - 25 mm² 025707	—	✓	✓	—	—	—	—
10 m - 25 mm² 056626	—	—	—	—	—	✓	—
Texas/NATO 3.5 m - 50 mm² 025653	—	—	—	—	—	—	✓
Anderson/NATO 2 m - 50 mm² 026803	—	—	—	—	—	—	✓
3 m - 50 mm² 072589	—	—	—	—	✓	—	—
2pts/NATO 5 m - 4 mm² 025837	—	—	—	—	✓	—	—
2pts/NATO Spiral 5 m 028968	—	—	—	—	✓	—	—



BATTERIES DE TRACTION : PRODUITS COMPATIBLES
Compatible Products - Kompatible Produkte



		TYPE	6 h	7 h	8 h	9 h	10 h	11 h	12 h	13 h	14 h	CURRENT
24 V	BATIOUM 25.24 X	liquid	75 Ah	90 Ah	120 Ah	125 Ah	130 Ah	140 Ah	155 Ah	165 Ah	180 Ah	25 A
	GYSFLASH 30.24 HF	liquid	—	—	—	75 Ah	85 Ah	105 Ah	125 Ah	145 Ah	175 Ah	15 A
		gel	—	—	—	—	—	75 Ah	85 Ah	105 Ah	120 Ah	
	GYSFLASH 50.24 HF	liquid	—	—	—	250 Ah	290 Ah	350 Ah	410 Ah	480 Ah	550 Ah	50 A
		gel	—	—	—	—	—	260 Ah	290 Ah	340 Ah	400 Ah	
	GYSFLASH 51.12	liquid	130 Ah	150 Ah	180 Ah	210 Ah	240 Ah	270 Ah	310 Ah	350 Ah	390 Ah	25 A
		gel	—	—	130 Ah	150 Ah	160 Ah	180 Ah	200 Ah	220 Ah	240 Ah	
	GYSFLASH 101.24	liquid	390 Ah	470 Ah	550 Ah	630 Ah	720 Ah	820 Ah	930 Ah	1050 Ah	1200 Ah	100 A
		gel	—	—	400 Ah	450 Ah	500 Ah	560 Ah	610 Ah	670 Ah	720 Ah	
	GYSFLASH 103.24	liquid	490 Ah	580 Ah	680 Ah	790 Ah	900 Ah	1020 Ah	1160 Ah	1310 Ah	1500 Ah	100 A
		gel	—	—	500 Ah	560 Ah	630 Ah	700 Ah	760 Ah	830 Ah	900 Ah	
36 / 48 V	GYSFLASH 25.48	liquid	130 Ah	150 Ah	180 Ah	210 Ah	240 Ah	270 Ah	310 Ah	350 Ah	390 Ah	25 A
		gel	—	—	130 Ah	150 Ah	160 Ah	180 Ah	200 Ah	220 Ah	240 Ah	
	GYSFLASH 51.48	liquid	260 Ah	310 Ah	360 Ah	420 Ah	480 Ah	540 Ah	610 Ah	690 Ah	790 Ah	50 A
		GYSFLASH 53.48	gel	—	—	260 Ah	300 Ah	330 Ah	370 Ah	400 Ah	440 Ah	



100 A		Cables Anderson 175A/Texas
100 A		Cables REMA 160A/Texas
15 A		Cables REMA 160A/Anderson
50 A		Cables Anderson 175A/Anderson
50 A		Cables Anderson 175A/Anderson

BOOSTERS

LITHIUM

INSIDE

 SPECIAL HOBBY • Non professional use •
Utilisation non professionnelle • Nicht für gewerblichen
Gebrauch.



-  START ENGINE
-  POWER BANK
- 
-  LIGHT



12 V

NOMAD POWER VAC 350

400 A

0,26 m - 5,26 mm² → AWG10

028937



NOMAD POWER 300

350 A

0,28 m - 5,2 mm² → AWG10

025875



ACCESSORIES
included for NOMAD POWER VAC 350

SMART CABLE
MULTI SECURITIES



ACCESSORIES
included for NOMAD POWER 300



NOMAD POWER 400

500 A

0,28 m - 5,2 mm² → AWG10

025882



ACCESSORIES
included for NOMAD POWER 400



NOMAD POWER 500

550 A

0,4 m - 8,3 mm² → AWG8

027145



ACCESSORIES
included for NOMAD POWER 500



NOMAD POWER PRO 700

600 A

0,26 m - 8,3 mm² → AWG8

027510



ACCESSORIES
included for NOMAD POWER PRO 700



SMART CABLE
MULTI SECURITIES

12 / 24 V

NOMAD POWER PRO TRUCK

600 A

0,55 m - 13,3 mm² → AWG6

027527



ACCESSORIES
included for NOMAD POWER 500



12 V

NOMAD POWER PRO 12 XL

1000 A

0,8 m - 21 mm² → AWG4

025912



24 V

NOMAD POWER PRO 24 XL

1400 A

0,8 m - 21 mm² → AWG4

025905



ACCESSORIES
included for

NOMAD POWER PRO 12 XL
NOMAD POWER PRO 24 XL



LITHIUM			I			J (3s)	 START PETROL & DIESEL	 CABLE	 MULTI SECURITIES	 INPUT	 MICRO USB	 OUTPUT	POWER BANK			 cm	 kg
CAPACITY/CELL	TYPE	FULL CHARGE	Start (6V)	Cranking CC	Peak Battery								  		OBD		
2.5 Ah - 37 Wh	NMC	5 h	400 A	800 A	1000 A	9000 J	12V	5V-2 A	●	5V/2 A	5V/2 A (Type C)	5V/2 A	●	2	—	27.2 × 0.65	0.48
2.5 Ah - 37 Wh	NMC	5 h	350 A	700 A	900 A	8000 J	12V	12V 5V-2.1 A	●	5V/2 A	—	5V/9V/12V - 5V/2 A	●	2	—	14.6 × 7.8 × 3.1	0.365
3 Ah - 45 Wh	NMC	5 h	500 A	1000 A	1200 A	11000 J	12V	12V 5V-2.1 A	●	5V/2 A	—	5V/9V/12V - 5V/2 A - 15V/5A	●	2	—	17.5 × 8.4 × 3.1	0.498
5.25 Ah - 77.7 Wh	NMC	6 h	550 A	1300 A	1500 A	12000 J	12V	12V 5V-2 A	●	5V/2 A 9V/2 A	—	5V/1A - 5V/2.1 A	●	2	—	22.5 × 9.1 × 3.4	0.610
6 Ah - 92.5 Wh	NMC	9 h	600 A	1500 A	2000 A	14000 J	12V	—	●	9V/2 A 12V/1.5 A	5V/2 A (Type C)	5V/2.4 A - 9V/2 A 12V/1.5 A - 15V/10 A	●	2	—	22.8 × 10 × 3.8	0.82
5.3 Ah - 137 Wh	NMC	10 h	600 A	1500 A	2000 A	12V : 14000 J 24V : 35000J	12V/24V	—	● Integrated	9 V/2 A 12 V/1.5 A	5V/2 A (Type C)	5V/1 A - 5V/2.1 A - 12V/10 A	●	2	●	24.8 × 24.8 × 9.6	2.4
8 Ah - 118.4 Wh	NMC	5 h	1000 A	1800 A	3000 A	22000 J	12V	12V/15 A 4 A	—	18V/2 A	—	5V/2.1 A - 12V/3.5 A 12V/10 A - 19V/3.5 A	●	2	●	27.4 × 27.8 × 11	5.6
8 Ah - 236.8 Wh	NMC	10 h	1400 A	2400 A	3000 A	60000 J	24V	12V/15 A 4 A	—	18V/2 A	—	5V/2.1 A - 12V/3.5 A 12V/10 A - 19V/3.5 A	●	2	●	27.4 × 27.8 × 11	5.6

																	
Recommendation																	
NP VAC 350	5 > 70 Ah																
NP 300	5 > 70 Ah																
NP 400	5 > 90 Ah																
NP 500	5 > 120 Ah																
NP 700	5 > 140 Ah																
NP PRO TRUCK	5 > 140 Ah												Max capability ( minimum charge needed)				
NP PRO 12XL	5 > 180 Ah																
NP PRO 24XL														> 240 Ah			



BOOSTERS

SUPER CAPACITOR

INSIDE

BATTERYLESS - SANS BATTERIE
- OHNE BATTERIE

NEW TECHNOLOGY - FULL ELECTRONIC CONTROL



- ✓ NO BATTERY INSIDE
- ✓ NO MAINTENANCE
- ✓ ALWAYS READY
- ✓ BOOSTER SANS BATTERIE INTERNE
- ✓ AUCUNE MAINTENANCE
- ✓ TOUJOURS PRÊT
- ✓ KEINE INTERNE BATTERIE
- ✓ KEINE WARTUNG
- ✓ IMMER BEREIT



-40/+65°C

STARTRONIC 800

800 A

12 V

60 > 5 V

026735



5×
800
F

INCLUDED

CIGARETTE LIGHTER
for Easy charge
STARTRONIC 800
& HYBRID 950
027404

12 V

Digital control



STARTRONIC HYBRID 950

SUPERCAPACITORS + LITHIUM

950 A

12 V

60 > 1 V

026117



INCLUDED
STARTRONIC HYBRID 950

Lithium battery



027411



SMART
SECURITY
POWER


5×
950
F + Lithium INSIDE

MADE
IN CHINA


MADE
IN FRANCE

							 INPUT CHARGE  Charging time								 cm	 kg
	I				Number of Capacitors	Integrated Inverter	 12 V		 12 V / 10 A		 5 V / 2 A		internal lithium battery			
	1V/C	START ICC	Peak				 OFF	 ON	 OFF	 ON	MICRO USB Type B					
STARTRONIC 800	800 A	1 400 A	—	12 V	5 × 800 F	●	4 min	60 s	4 min	4 min	5 V/2 A	40 min	—	26,7 × 19,5 × 5	1,86	
STARTRONIC HYBRID 950	950 A	1 660 A	—	12 V	5 × 950 F	●	4 min	60 s	4 min	4 min	5 V/2 A	40 min	30 min	25 × 18,5 × 6	1,86	
GYSCAP 680E 	1 600 A	2 700 A	9 000 A	12 V	5 × 3000 F	●	15 min	2 min	15 min	15 min	—	—	—	35 × 44 × 19	8,2	
GYSCAP 24V 	2 500 A	4 500 A	10 000 A	24 V	10 × 3000 F	●	15 min	2 min	30 min	30 min	—	—	—	32 × 49 × 21.5	12	

SUPERCAPACITORS




1 MILLION
CYCLES



ULTRA FAST
CHARGE



NO CHARGE
STORAGE



UNLIMITED
STARTS

SMART STARTER



FULL PROTECTION

-40/+65°C

SMART STARTER
MANAGEMENT SYSTEM



12 V

5×
3000
F

GYSCAP 680E

1600 A

12 V

60 > 1 V

026773

1.7 m - 25 mm²
Cables 100% Cu



Homologations / Approvals / Zulassungen:
PSA17.1716

24 V

10×
3000
F

GYSCAP 24V

2500 A

24 V

60 > 2 V

028944

2 m - 50 mm²
Cables 100% Cu

INCLUDED

CIGARETTE LIGHTER
for Easy charge

1.5 m



12 V

GYSCAP 680E / GYSCAP 24V

OPTION

GYFLASH
4.12
p.6



F5
p.14



GYSCAP 680E / GYSCAP 24V

i Recommendation											
STARTRONIC 800	5 < 90 Ah										
STARTRONIC HYBRID 950	5 < 100 Ah										
GYSCAP 680 E	5 < 150 Ah										
GYSCAP 24V											225 Ah



BATTERY TESTERS POWER INVERTER PORTABLE ENERGY

TRADITIONAL TESTERS	64
DIGITAL TESTERS	64
TESTERS & PRINTER	66

POWER INVERTER	68
PORTABLE ENERGY	70



TBP



WIRELESS / BT

TESTERS TRADITIONAL

TESTERS DIGITAL

×4
Languages
Sprachen

×13
Languages
Sprachen

COLOR SCREEN

ALTERNATOR

CAR & MOTORCYCLE TEST



WAVEFORM



REVIEW WAVEFORM HISTORY

×12
Languages
Sprachen

NEW
07 2023

DBT 500

6/12 V 7 > 240 Ah

ALTERNATOR 12/24 V

079823

TBP 100

6/12 V 20 > 100 Ah

055131



TBP 500

12 V 10 > 160 Ah


055148



Wireless battery monitor
Indicateur de charge sans fil

12/24 V 7 > 240 Ah

024212



BTW 6V/12V

6/12 V 7 > 240 Ah

ALTERNATOR 12/24 V

077355



BT 001

12 V 7 > 230 Ah

056640



NBT 100

12 V 20 > 150 Ah

024151




NBT 200

12 V 20 > 150 Ah

ALTERNATOR 12 V

024168



×1
Languages
Sprachen



DBT 300

12 V 4 > 150 Ah

ALTERNATOR 12 V

024175



×10
Languages
Sprachen



DBT 350

12 V 7 > 240 Ah

ALTERNATOR 12/24 V

025868



Languages - Sprachen

	GB	FR	DE	IT	ES	PT	CZ	NL	PL	RU	CN	TR	JP	KR	IR
DBT 300															
DBT 350															
DBT 500															
PBT 550															
PBT 600															
PBT 700															
BT 2010															
PBT 812															
PBT 824															
BTW 6V/12V															

YouTube



PLAYLIST
BATTERY
TESTERS

MADE
IN CHINA

MADE
IN TAIWAN

MADE
IN CHINA

Approvals
Homologations
Zulassungen



0.65 m



1.2 m



1.8 m



1.8 m



LCD COLOR

1.8 m

x2 (included)
056633

x2 (included)
056633

Standard

Clamps
056510

						
	056220	x2	37 mm	7.5 m	25 mm	BT 301 / BT 501 / BT 551
	056237	x1	57 mm	28 m	50 mm	RT 777 / PBT 700 / PBT 812 / PBT 824 / BT 2010
	056633	x2	57 mm	7.5 m	25 mm	PBT 550 / PBT 600 / PBT 700 / PBT 812 / PBT 824 / BT 2010 / SP

			TEST				DIGITAL							
					CHARGE & START SYSTEM VEHICLE 									L × W × H cm / kg
PBT 550	12 V	30 > 220 Ah	•	min 6 V	12 V	•	back-lit/rétro-éclairé	1s	instant	•	—	0.55	55 × 25	29 × 23 × 9 / 0.9
PBT 600	12 V	30 > 220 Ah	•	min 8 V	12 / 24 V	•	back-lit/rétro-éclairé	1s	instant	•	—	1.1	55 × 25	29 × 23 × 9.5 / 1.3
PBT 700	12 V	7 > 240 Ah	•	min 8 V	12/24 V	•	back-lit/rétro-éclairé	1s	instant	•	—	0.7	23,5 × 10.2 × 6.8	40.5 × 28 × 9 / 1.9
BT 2010 DHC	6-12 V	7 > 240 Ah	•	min 1.5V	12/24 V	•	back-lit/rétro-éclairé	1s	instant	•	6 x 1.5 V LR6-AA	0.7	13 × 6.4 × 25.1	47.6 × 34.4 × 11.8 / 3
PBT 812	6-12 V	7 > 240 Ah	•	min 1.5V	12/24 V	•	color TFT display 2.8"	1s	instant	•	6 x 1.5 V LR6-AA or 18650 lithium battery(not included)	0.7	28 × 14 × 7.5	—
PBT 824	6-12 -24 (2x12) V	7 > 240 Ah	•	min 1.5V	12/24 V	•	back-lit 4 colors /rétro-éclairé	1s	instant	•	6 x 1.5 V LR6-AA	0.7	25 × 4.5 × 13	40 × 28 × 9 / 2.3

 <i>Recommendation</i>	TEST			 PRINT PAPER											CURRENT CCA SAE	
	Battery/Batteries/ Ladegeräte	Alternator Circuit/ Circuit alterateur/ Lichtmaschinen Schaltkreis			LIQUID	START/STOP ENGINE	EFB	AGM VRLA/GEL								
PBT 550			12 V	•	•	•	•	•			30 > 220 Ah				100 > 2000 A	
PBT 600			12 V	•	•	•	•	•			30 > 220 Ah				100 > 2000 A	
PBT 700			12 V	•	•	•	•	•	7 > 240 Ah		7 > 240 Ah				40 > 2000 A	
BT 2010 DHC			12 V	•	•	•	•	•	7 > 240 Ah							40 > 3000 A
PBT 812			12 V	•	•	•	•	•	7 > 240 Ah							25 > 3000 A
PBT 824	 (2X12)		12 V	•	•	•	•	•	7 > 240 Ah							40 > 2000 A



CONVERGYS / PSW / MSW

POWER INVERTER

12/24 V DC > 230 V AC



PSW REMOTE CONTROL

For 601W-12



6 m



For 1002W RC-12, 1502W RC-12, 2002W RC-12, 2002W RC-24






6 m

Input = 888 V
Output = 888 W

MSW / PSW TECHNOLOGY



- Low volt / Over volt / Over load / Overheating / Output short-circuit
- Tension faible / Sur tension / Surcharge / Surchauffe / Court-circuit
- Unterspannung / Überspannung / Überlastung / Überhitzung / Kurzschluss am Ausgang



SELECT THE RIGHT POWER INVERTER

- CHOISISSEZ VOTRE CONVERTISSEUR
- WÄHLEN SIE IHREN WECHSELRICHTER

	CONVERGYS 150	CONVERGYS 300	PSW 601W RC-12	PSW 1002W RC-12	PSW 1502W RC-12	PSW 2002W RC-12	PSW 2002W RC-24	MSW 82000	70 Ah	200 Ah
12 V										
24 V										
HOME APPLIANCE - ÉLECTROMÉNAGER										
Microwave - Micro-Ondes - Mikrowelle							700 - 1000 W	30 - 50 min	1 h 30 - 2 h	
Toaster - Grille Pain							800 - 1500 W	20 - 40 min	1 h - 2 h	
Fridge - Réfrigérateur - Kühlschrank (40 L)							45 W	12 h	35 h	
Kettle - Bouilloire - Wasserkocher							700 - 2500 W	15 - 45 min	35 min - 2 h	
Espresso coffee maker - Cafetière espresso - Espresso-Maschine							1000 - 1600 W	20 - 30 min	1 h - 1 h 30	
Drip coffee maker - Cafetière filtre - Filterkaffee-Maschine							800 - 1200 W	25 - 40 min	1 h 30 - 2 h	
ELECTRONIC - ÉLECTRONIQUE										
Mobile phone - Téléphone - Telefon							5 - 10 W	55 - 110 h	155 - 310 h	
Laptop - Ordinateur portable							60 - 95 W	5 - 9 h	16 - 28 h	
Radio							10 - 40 W	14 - 55 h	40 - 155 h	
TV 15"							40 W	13 h 30	39 h	
TV 21"							50 W	11 h	31 h	
Video game console - Console de jeux vidéo - Konsole für Videospiele							39 - 100 W	5 - 13 h	16 - 39 h	
Camera - Appareil photo - Fotoapparat							4 - 19 W	25 - 135 h	78 - 390 h	
-COMFORT - CONFORT										
Light - Eclairage - Beleuchtung							100 W	5 h 30	16 h	
Electrical heater - Chauffage électrique - Elektrische Heizung							1800 - 2500 W	12 - 20 min	35 - 45 min	
Fan - Ventilateur - Lüfter							50 W	11 h	31 h	
Hairdryer - Sèche cheveux - Fön							1000 - 2000 W	15 - 30 min	45 min - 1 h 30	
SAILING - NAUTISME										
Navigation lights - Feux de navigation - Navigationslichter							24 W	30 h	80 h	
Radar							24 W	30 h	80 h	
Autopilot mode - Pilote automatique							60 W	9 h	30 h	
GPS/Sat nav. - GPS							6 W	110 h	310 h	

* Usage duration (h) = $\frac{80\% \times \text{Capacity (Ah)} \times \text{Optimum Efficiency (\%)} \times \text{Input DC (V)}}{\text{Power (W)}}$

MADE IN CHINA	Power	Peak power	Pure Sin Wave	Optimum Efficiency	Input DC	Output AC	Output USB (2.1) DC	max 150W	1.5 mm²	2.5 mm²	Universal	5 m	2,2 kg	26.5 × 17 × 7.5	31 × 22 × 12 / 2.3
CONVERGYS 150	150W	300W	—	90,5 %	12V	230V	5V · 2 A	•	—	1.5 mm²	•	—	0,5 kg	N/A	8 × 16.5 × 24.7 / 0.45
CONVERGYS 300	300W	600W	—	85 %	12V	230V	5V · 2 A	•	•	2.5 mm²	•	—	0,95 kg	N/A	21.3 × 20 × 6.8 / 0.95
PSW 601W RC-12	600W	1200W	•	90 %	12V	230V	5V · 2 A	—	cables	6 mm²	•	•	5 m	4,7 kg	37.5 × 21 × 10
PSW 1002W RC-12	1000W	2000W	•	90 %	12V	230V	5V · 2 A	—	cables	10 mm²	•	•	5 m	5 kg	37.5 × 21 × 10
PSW 1502W RC-12	1500W	3000W	•	90 %	12V	230V	5V · 2 A	—	cables	16 mm²	•	•	5 m	6,25 kg	38.5 × 25 × 10
PSW 2002W RC-12	2000W	4000W	•	90 %	12V	230V	5V · 2 A	—	cables	22 mm²	•	•	5 m	6,25 kg	38.5 × 25 × 10
MSW 82000	2000W	4000W	—	80 %	24V	230V	5V · 2 A	—	cables	12 mm²	•	•	—	5,8 kg	35 × 20 × 28
PSW 2002W RC-24	2000W	4000W	•	90 %	24V	230V	5V · 2 A	—	cables	12 mm²	•	•	5 m	6,25 kg	38.5 × 25 × 10

12 V CONVERGYS

CONVERGYS 150
027022
027039



CONVERGYS 300
027053
027046



12 V PSW PURE SINE WAVE

PSW
601W RC-12

067332
067349

PSW
1002W RC-12

067356
067363



PSW
1502W RC-12

067370
067387



PSW
2002W RC-12

067394
067400



24 V MSW MODIFIED SINE WAVE



MSW 82000

027237
027244

24 V PSW PURE SINE WAVE



PSW
2002W RC-24

067417
067424


INCLUDED
FOR ALL



48 cm



48 cm



1 m



JUMPER CABLES EV CABLES ACCESSORIES

JUMPER CABLES	74
EV CHARGING	75
ACCESSORIES	76

ACCESSORIES

CABLES EN 60245-6/H01N2-D (Rubber - Caoutchouc)		↔ L		A (60%)	A (35%)
	16 mm²	100 m ≲ x m	046252 046207	121	131
	25 mm²	5 m	045408	165	185
		100 m	046603		
	35 mm²	≲ x m	046306		
		100 m	046702	211	243
	50 mm²	≲ x m	046405		
		100 m	046801	275	323
	70 mm²	≲ x m	046757		
		≲ x m	046832	351	419
	95 mm²	≲ x m	046863	433	527

HIGH FLEXIBILITY ELECTRICAL CABLES		↔ L			A (60%)	A (35%)
	10 mm²	100 m 20 m	054882 056107	054875 056091	88	92
	16 mm²	100 m 20 m	054905 056121	054899 056114	120	130
		100 m 20 m	054929 056145	054912 056138	164	184
	25 mm²	100 m 20 m	054943 054967	054936 054950	210	240
		100 m 50 m	—	056565	310	380

Clamp-on ammeter
- Pince
ampèremétrique
- Strommesszange

400 A
053991
600 A
053984





CLAMPS - Pincas • Klemmen • Pinzas • Garras • Ακροδέκτες • Зажимы • 充电夹

	40 A	60 A	60 A	200 A	300 A	600 A	650 A	700 A	850 A	1000 A	300 A	600 A
I 100%	30 A	60 A	60 A	100 A	200 A	120 A	120 A	120 A	170 A	200 A	-	-
I peak	75 A	150 A	150 A	200 A	300 A	600 A	650 A	700 A	850 A	1000 A	-	-
max	↕ 30 mm	↕ 25 mm	↕ 25 mm	↕ 38 mm	↕ 45 mm	↕ 40 mm	↕ 35 mm	↕ 28 mm	↕ 44 mm	↕ 55 mm	↕ 38 mm	↕ 38 mm
max	2.5 mm²	10 mm²	10 mm²	16 mm²	25 mm²	35 mm²	25 mm²	25 mm²	35 mm²	70 mm²	50 mm²	95 mm²
												

BATTERY TERMINAL - Cosses batterie - Polklemmen - Terminales batería - Accupool - Terminais de bateria
- Πόλος μπαταρίας - Контакты аккумуляторной - батареи - 电池端子

⌀ 10 mm / 35 mm²			⌀ 13 mm / 50 mm²			⌀ 16 mm / 70 mm²		
	x1							
								
054400								

CABLE LUGS - Cosses - Terminal Kabelschuhe - Kabelschoen

	16 mm²	M10	x10	038219
	25 mm²	M10	x10	038226
	35 mm²	M14	x10	038233
	50 mm²	M14	x10	038240
	75 mm²	M16	x10	038257
	125 mm²	M15	x5	038264
	25 mm²	M5	x100	047525
	35 mm²	M6	x100	047532
	50 mm²	M10	x100	047549

CLEANING BRUSH POLES /
TERMINALES
- Nettoyeur cosses / bornes

	10 mm²	M16	x100	047501
	16 mm²	M15	x100	047518
	70 mm²	M10	x100	047556
	95 mm²	M10	x50	047570





DINZE CONNECTORS - Connecteurs Texas - Stecker - Conectores - Schakelears - Conectores

	I A max		mm²	mm	Ø mm	Compatibility		Ref.
	CFM 25.14	200	10/25	14	9	CM 25.14, CF 25.14	x1	045507
	CFM 50.21	300	35/50	21	13	CM 50.21, CF 50.21	x1	045606
	CFM 70.21	400	50/70	21	13	CM 70.21	x1	047488
	CM 25.14	200	10/25	14	9	CF 25.14	x20	045668
	CM 50.21	300	35/50	21	13	CF 50.21	x10	045613
	CM 70.21	400	50/70	21	13	CF 70.21	x5	045750
	CM 95.24	500	70/95	24	13	CF 95.24	x5	047495
	CF 25.14	200	10/25	14	9	CM 25.14	x30	045651
	CF 50.21	300	35/50	21	13	CM 50.21	x10	045620
	CF 70.24	400	50/70	24	13	CM 70.21	x5	045736
	CF 95.24	500	70/95	24	13	CM 95.24	x5	072374


QUICK CONNECTORS

	Ø 10 mm / 50 mm² I max = 1000 A 054455	
---	--	---

FUSES - Fusibles - Sicherungen - Fusibles - Zekeringen - Fusíveis - Ασφάλειες - Плавкие предохранители - 保险丝

	x5		x10		Ø10 mm 80 mm		x2		x2		x2		x2		x2
6.3 A 054578 10 A 056527		10 A 054530 15 A 054493 20 A 054509 25 A 054516 30 A 054523 40 A 054554		100 A 054486 100 A 054394		100 A 054394		150 A 027930		200 A 054547 250 A 055568 300 A 054561		200 A 054547 250 A 055568 300 A 054561		200 A 054547 250 A 055568 300 A 054561	

ANTI-ARC PROTECTION - Protection Anti-Arc - Lichtbogenschutz
- Protección anti-arco - Piekspanningsbeveiliging - Protecção anti-faísca
- Αντι-σπινθηρική προστασία - Защита против дуги - 抗电弧保护

	041318		12V		x2

ADJUSTABLE BATTERIE
CARRIER - Porte-batterie ajustable
- Einstellbarer Batteriehalter - Porta-
baterias ajustable - Переноска для
аккумулятора

	058354
---	--------

ACIDIMETER (PH METER) - Pèse acide antigel
- Säure/Frostschutzmittel-Tester - Acido densímetro
anticongelante - Zuurweger - Medidor de PH (ácido)
- Μετρητής οξύτητας (PH) - Ацидиметр (pH-метр)
- 防冻酸度计

	054103
---	--------

SOLAR POWERED CHARGER WITH ACCESSORIES

- Kit solaire de maintien de charge avec accessoires - Solarpanel zur
Ladeerhaltung mit Zubehör - Kit solar de mantenimiento de carga
- Солнечная панель для поддержания заряда в наборе с аксессуарами

	072411
--	--------

MULTI CHARGE STATION FOR BATTERIES

- Station multicharge pour batteries
- Multi-Ladestation für Starterbatterien

	072411
--	--------

MEMORY AUTO SAVE - Sauvegarde mémoire OBD - Sichtung des Speichers - Salvaguardia memorias
- Salvaguardas de memória - Αυτοματη αποθήκευση ρυθμίσεων - Сохранение настроек - 记忆储存器

	054998 055001	
---	------------------	---

HAND LAMPS - Lampes baladeuses - Handleuchte

Lampe BALADEUSE TRIPODE 250 L
100-250 lumens (x3)

3 x 1 W COB LED
3.3 V - 300 mAh
AAA rechargeable, NI-MH
USB charging (6h)
operating time
High position: 1 h
Low position: 3 h
Flashing: 5 h

26 x 10 x 10 cm / 960 g
20 x 10.5 x 27 cm

059955

Lampe BALADEUSE 400 L
400 lumens

COB LED
Li-ion
Charging time: 8h
operating time
High position: 2.5 h
Low position: 5 h
Top light (1 W): 6 h

23 x 6.5 x 4 cm / 480 g
13 x 7 x 23.5 cm

059153

Lampe BALADEUSE PRO 600 L
250-600 lumens

COB LED, 80 CRI
3.7 V - 2200 mAh Li-ion
micro USB charging (3.5 h)
operating time
High position: 1.5 h
Low position: 4.5 h
Top light (100 lumens): 10 h

19 x 5.6 x 2.9 cm
520 g
9 x 13 x 23.2 cm
IP54
210g

060883

UNDER BONNET LAMP - Lampe sous capot - Leuchte für Motorhaube

Lampe SOUS CAPOT 600 L
500-1000 lumens

120 COB LED
3.7 V - 4000 mAh Li-ion
charging time: 10/12 h
operating time
High position: 4 h
Low position: 8 h

26 x 10 x 10 cm
2.3 kg
23.5 x 12 x 69.5 cm

059962

130 > 180 cm

Lampe SOUS CAPOT 800 L
250-800 lumens

120 COB LED
3.7 V - 4000 mAh Li-ion
charging time: 10/12 h
operating time
High position: 3 h
Low position: 6 h

26 x 10 x 10 cm
2 kg
60.7 x 15 x 11.3 cm

058002

360° AMBIANT LAMP
- Lampe ambiance 360°

Lampe AMBIANCE 360° PORTABLE
1000 L
60 > 1000 lumens

>80 CRI SMD LED
6500 K
3.7 V - 5200 mAh Li-ion
USB charging (4.5 h) / USB power supply
operating time 2 > 27 h

26 x 7.5 x 7.5 cm
660 g
7.8 x 8 x 35 cm
IP 54

059764

360°

USB charging /Power supply

INSPECTION LAMP - Lampe inspection - Inspektionslampen

Lampe INSPECTION PRO 600 L
0 > 600 lumens

6500 K
3.7 V - 2600 mAh Li-ion
operating time
1.5 > 15 h

380 x 40 x 45 mm
360 g
40 x 8.8 x 5.5 cm

057760

120 lumens

charge indicator

180°

360°

Lampe INSPECTION MINI 350 L
0-350 lumens **NEW**

COB LED
3.7 V - 1100 mAh Li-ion
USB charging (3 h)
operating time
3 > 6.5 h

IP 20

075894

120 lumen

350 lumen

131 mm

146 mm

Lampe INSPECTION PRO 800 L
120-800 lumens **NEW**

COB LED
3.7 V - 2600 mAh Li-ion
USB charging (4 h)
operating time
2.5 > 9 h

IP 54

075900

120 > 400 lumen

150 > 800 lumen

94 mm

108 mm

Lampe INSPECTION FRONTALE 280 L
100-280 lumens

3 W COB LED
80 CRI+, 6500 K
3.7 V - 1500 mAh Li-po
micro USB charging
operating time
High position: 2 h
Low position: 6 h

IP 65 / 17.8 x 4.7 x 4.2 cm
40 x 8.8 x 5.5 cm / 200 g

060845

motion detection mode

60°

Lampe INSPECTION MINI 200 L
100-200 lumens

COB LED, 80 CRI, 6500 K
3.7 V - 700 mAh Li-ion
micro USB charging (2.5 h)
operating time
High position: 1.5 h
Low position: 4 h
Top light: 3.5 h

IP 20 / 17.4 x 2.7 x 2.8 cm
17.5 x 5 x cm / 140g

060852

120 lumens

360°

WORKLIGHT WITH TRIPOD
- Projecteur sur trépied
- Arbeitsleuchte mit Standfuß

Lampe sur TRÉPIED 1800 L
1800 lumens

3 x 55 COB LED
total 165 LED
1.8 m power cord

3.2 kg
95 x 14.5 x 14 cm

059146

adjustable 1.3 m max

Lampe sur TRÉPIED 3000 L
3000 lumens

35 W COB LED
2 m power cord

IP 44
4.1 kg
103 x 21.5 x 10 cm

059979

adjustable 1.5 m max

Lampe sur TRÉPIED 4000 L
4000 lumens

3 x 20 COB LED,
total 60 LED
3 m power cord

6.4 kg
22 x 16 x 116 cm

059986

adjustable 2.3 m max

2.3 m max

AUTOMOTIVE BATTERIES

Batteries de démarrage - Starterbatterien - Baterias de arranque
- Automotive accu's - Baterias de Automóvel - Μητροπλες
αυτοκινητων - Пусковые батареи - 汽车启动电池

Curves	LIQUID Calcium / Silver	Start & Stop / AGM / EFB / GEL / Optima	Unattended charge	100% charged	Maintenance	Battery desulphation	Fast Charge	Fast Charge ++
W	✓	-	-	-	-	-	-	-
W2	✓	-	✓	-	-	-	-	-
WU	✓	-	✓	-	✓	-	-	-
WUoU	✓	✓	✓	✓	✓	-	-	-
IWUoU	✓	✓	✓	✓	✓	✓	✓	-
I REGULATED FAST CHARGE IUoU	✓	✓	✓	✓	✓	-	✓	✓
7 STEP GYSFLASH Pb	✓	✓	✓	✓	✓	✓	✓	✓

GYSFLASH Lithium





8 STEP Li-ion

8 STEP LiFePO₄

9 STEP Li-ion

9 STEP LiFePO₄

LiFePO₄ / Li-ion / Li-Po / NMC / LCO / MCO / NCA...



MARKETING




Catalogs and posters available
for download on our website
www.gys.fr



A - Barnum
3 x 3 m
098022

B - Open
Barnum
2 x 2 m
098039

C - Oriflamme
3 x 0.50 m
098015



Display stand - Podium de
présentation - Podest
(machines not included)

063204
A: 45 cm, B: 50 cm, C: 50 cm

063211
A: 80 cm, B: 50 cm, C: 50 cm



Retail display space with 2 shelves
- Linéaire de vente avec 2 étagères
- Lochwandregal mit 2 Böden
(machines not included)

060784



Type	FA1	FA2	SB1
complete - complet - komplett	062429	062443	061149
without display stand - sans linéaire - ohne Regal	062436	062450	062412



INVEST IN THE FUTURE



French manufacturer
since 1964

2
0
2
4

Chargers, Boosters & Starters

Charge & entretien des batteries

Batterieservicegeräte-Katalog

Caricabatterie, Booster & Avviatore

Catálogo de Cargadores



GYS FRANCE

HEADQUARTERS

1 rue de la Croix des Landes
CS 54159
53941 Saint-Berthevin - Cedex
Laval - France
Tel +33 2 43 01 23 60
E-mail service.client@gys.fr



ZI, 134 bd des Loges
53941 Saint-Berthevin
Laval - France

LOGISTIC CENTER

2 Rue Jean Dausset
53810 Changé - France
Tel +33 2 43 01 54 33



GYS GERMANY

Professor-Wieler
Straße 11
52070 Aachen
Deutschland

Tel +49 241/189-23-710
Fax +49 241/189-23-719
E-mail aachen@gys.fr



GYS ITALIA

Via Porta Est, 7
30020 Marcon - VE
Italia

Tel +39 041 53 21 565
E-mail italia@gys.fr



GYS CHINA

Lot N°15
6666 bd Songze
201706 Qingpu
Shanghai
China

Tel +86 6221 4461
Fax +86 5226 0067
www.gys-china.com.cn
E-mail
contact@gys-china.com.cn



GYS UK

Unit 3 - Great Central Way
Rugby - Warwickshire
CV21 3XH
United Kingdom

Tel +44 1926 338 609
Fax +44 1926 429 764
E-mail uk@gys.fr



GYS IBÉRICA

Avenida Pirineos 31
Nave 9
San Sebastian de los Reyes
28703 Madrid
España

Tel +34 917 409 790
E-mail iberica@gys.fr



LinkedIn
 Youtube
 WeChat
 Facebook
 Instagram

www.gys.fr

Distributed by

